ARCHITECTURAL DETAILS

FOR EVERY TYPE OF BUILDING

FOR
CONTRACTORS
BUILDERS
LUMBER DEALERS
MILL MEN
DRAFTSMEN
ARCHITECTS

Wm. A. RADFORD
CHICAGO, ILL.

The Gift of

ANNA M. SCHWEINFURTH
TRUST

to the
CLEVELAND
PUBLIC LIBRARY
FINE ARTS DEPARTMENT

1921

245.

ARCHITECTURAL DETAILS

FOR EVERY TYPE OF BUILDING

A Practical Drafting Room Guide for Contractors, Builders, Lumber Dealers, Millmen, Draftsmen, and Architects.

By

William A. Radford, President of the Radford Architectural Co.; Editor-in-Chief "American Builder" and "Farm Mechanics"; Publisher "Radford's Cyclopedia of Construction" in twelve volumes; "Radford's Estimating & Contracting"; "Details of Building Construction"; "Guaranteed Build-Plans", Etc., Etc. . . .

Copyright1921,
By the Radford Architectural Co.

THE RADFORD ARCHITECTURAL COMPANY,
CHICAGO, ILLINOIS

CLEVELAND PUBLIC LIBRARY

FOREWORD

THIS present volume is intended to supplement our well-known collection of building details, entitled "Radford's Portfolio of Details of Building Construction," which was first issued in 1912 and has since run thru many editions.

All of the plates in the present series are new—not duplicating at all the earlier work. They present many of the modern ideas, that have come to the front during the past ten years.

This collection of details is offered with the expectation and hope that it will be of great practical utility to carpenters, builders, mill men, lumber dealers, draftsmen and architects. The aim has been to make it a complete manual of modern building practice, all points being made clear and understandable by means of the working drawing—the language of the blue print and the universal language of the building trades.

This book is a collection of plates, accurately drawn by skilled draftsmen, showing clearly the details of modern building construction and finish. Brief explanatory text accompanies each plate, calling attention to some of the points illustrated. The drawings themselves, however, are of first importance and should be carefully studied. More helpful ideas and exact information are contained in a single one of these plates of details than could be crowded into a whole chapter of ordinary descriptive text.

Details are given showing the framing and construction of residences of every type—frame houses, brick houses, brick veneer houses, stucco houses, etc. Also every popular and attractive style of interior trim is fully detailed. Special ideas are presented for the appropriate interior finish for every room or part of the house. These ideas are worked out complete, the drawings showing both the arrangement of the room and all the interior trim, including built-in features, fully detailed.

This is the day of "built-in" space and labor-saving features in the home. Carpenters and builders are called on continually to plan and build buffets and sideboards for the dining room; kitchen cabinets, cases, and cupboards for the kitchen and pantry; wardrobes and linen closets for the chambers; and window seats, fireplaces with decorative mantels, and built-in bookcases for the living room and library. These drawings have been prepared to show exactly how this kind of work is done. Many practical ideas are embodied in them; and new and attractive designs are presented from which the carpenter, the architect, or the builder can draw for all or any of these.

Many valuable details are also included in this collection of special interest to the country carpenter and builder. These include barn framing details of all kinds, ice-house and cold storage construction, silo building, etc.

The practical utility of detail plates of this kind will probably be best appreciated by those who draw plans or who are called upon to make their own designs for building work. The drawings in this collection have been prepared to meet especially the needs of such workmen.

Especial attention is called to the Index. This has been made very complete, all the various features detailed on any of the plates being listed and cross-indexed so that they may be very quickly found, without the necessity of searching thru the entire work. Since all the plates are completely indexed for ready reference their full value is available for use by the busy man.

Logical Methods in Architectural Drafting

A KNOWLEDGE of architectural drafting is vitally essential to the carpenter, builder or contractor, who would develop both himself and his business to the greatest possible extent.

The builder who is able to work out a neat and accurate set of drawings or "plans" fully dimensioned and detailed, leaving nothing to chance, has a very decided advantage over his brother, who, without fully conceived ideas and plans, starts building, and trusts to luck and good fortune that everything will work out all right. Even rough sketch drawings with approximate dimensions are better than none, but only full and detailed sets of plans are advisable.

In evolving a set of working plans the first logical step is the sketch. The purpose of the sketch is to fix the various ideas of either the builder or his client or of both and to give some definite basis for a start.

The medium for the sketch may be either pencil, pen and ink, water color or wash, the first named being the most common and the simplest to use.

The value of the sketch to the "builder architect" can hardly be over-estimated, because if well and attractively done, it may bring valuable contracts, which might not be obtained if this means of expression were not used.

Preliminary or "thumb nail" sketches, as they are sometimes called, should not be over 3 or 4 inches in size. They are not drawn to any definite scale and their chief purpose is to show arrangement. They should, however, be kept in proportion as much as possible.

The type of plan for such a sketch must of course be determined upon before the first drawing is made and the deciding factors are, first, the character of the site, and, second, the style of the exterior.

If we analyze any number of house plans we will find that they may be broadly classified into two general types, namely, the central entrance or central hall type, and the side entrance or side hall type. In the first named, as illustrated (Fig. 1), we have a symmetrical arrangement of rooms opening from a central hallway. This is the typical "Colonial" plan and calls, as a rule, for that style of elevation. In Fig. 2 we have the second type shown; note that in this type we have a plan that is unsymmetrical and is adapted especially to the narrow city lot.

We will take as an illustration of the logical steps to follow in making a sketch the first type, or central hall plan. First determine the approximate proportion of the floor plan, says two as to three. 1. Sketch center line. 2. Draw front and rear outside wall lines representing the width of the wall by a single line. 3. Side wall lines. 4. Locate main partition lines. 5. Minor partition lines. 6. Rough in approximate position of openings, doors and windows.

Study carefully at this time the relation of rooms and the circulation.

In like manner sketch second floor plan. It will be found that the basement, as a rule, logically takes its arrangement from the first floor plan, so we need not consider it in the first sketch.

After line sketches of the plans are made, the front elevation and then principal side elevation should be drawn.

The style of the exterior having been decided, determine first the proportion of the front wall—that is, the height from the ground to the under side of the cornice compared with the width. This height in the ordinary two-story house varies from 20 to 24 feet.

1. Block in this rectangle with center line.
2. Block in height lines for windows and doors.
3. Draw vertical outside lines for windows and doors, determining their positions approximately from plans.
4. Draw roof, taking height as ¼, ⅓ or ½ depth of plan, depending on judgment of designer.
5. Draw in porch or porches according to style of exterior.
6. Darken or shade window openings and show shadow under cornice.
7. Sketch in background.









FIG-4

Illustrating Logical Method of Developing the Floor Plans of a Residence.

TYPICAL ELEVATION DETAILS





BLOCKING IN ELEVATIONS



FIG 4

DEVELOPMENT OF FRONT ELEVATION

Illustrating Logical Method of Developing the Elevations of a Residence.

DEVELOPMENT OF DETAILS

BOX SILL CONSTRUCTION



FIG. 1



FIG. 2



FIG. 3



FIG. 4

BOX CORNICE CONSTRUCTION

FIG.1



FIG. 2



FIG 3

DOUBLE HUNG WINDOW CON STRUC TION

SCALE
6" 3" 1'0"



FIG.1



FIG.2



FIG 8

Illustrating Logical Method of Handling Construction Details of a Residence.

DEVELOPMENT OF THE PERSPECTIVE



The Fundamentals of Architectural Perspective Drawing.

DETAILS OF CONSTRUCTION FOR RETARDING FIRE



FIG. 1 - ELEVATION SHOWING FIRE STOPPING IN FRAME WALL AT CONNECTION OF UPPER FLOOR JOISTS WITH RIBBON.

FIG. NO. 1



FIG. NO. 4

FIG. 4 - CONNECTION OF ATTIC CEILING JOISTS WITH ROOF RAFTERS, FIRE STOPPING SUPPORTED ON BOARDS FITTED BETWEEN RAFTERS + CEILING JOISTS.



FIG. NO. 2

IF BRICK IS USED - THE BOARDS + NAILING PIECES ARE NOT REQUIRED.



FIG. 5 - INTERIOR PARTITION RUNNING SAME DIRECTION AS FLOOR JOISTS SUPPORTED ON DOUBLE JOISTS, FIRE-STOPPED AT BOTTOM BY 2X4" SOLE.

FIG. NO. 5



FIG. NO. 7

FIG. 7. CONNECTION OF FLOOR JOISTS WITH OUTSIDE FRAME AT PLATE LEVEL, SHOWING "OPEN RAFTER END" CORNICE + FIRE STOPPING SUPPORTED ON BOARD CUT BETWEEN JOISTS.

FIG. NO. 8

FIG. 8. PARTITION RUNNING CROSSWISE TO FLOOR JOISTS, FOOTING ON SOLE USED AS A FIRE-STOP. THIS WOULD BE IMPROVED BY ADDITION OF SOME INCOMBUSTIBLE MATERIAL ON TOP OF SOLE.



FIG. NO. 3

FIG. 2+3 - ELEVATION + PLAN SHOWING FIRE-STOPPING OF WALL OF FRAME BLD'G AT LINE OF SILL + BETWEEN STUDS + FLOOR JOISTS.



FIG. 6 FIRE STOPPING OF PARTITION RESTING ON WOOD GIRDER.

FIG. NO. 6



FIG. NO. 9

FIG 6 FIRE-STOPPING WITH TIMBER CUT BETWEEN FLOOR JOISTS ON TOP OF BRICK PARTITION

DETAILS OF FIRE-RETARDING CONSTRUCTION



FIG. NO. 1

FIG. #1 SHOWING ORDINARY FLOOR FRAMING AROUND A CHIMNEY ALL TIMBERS 2" CLEAR OF BRICK-WORK AND SPACE FILLED WITH FIRE-PROOFING MATERIAL



FIG. NO. 2

FLOOR FRAMING AROUND A SINGLE FIREPLACE. NOTE FILLING BETWEEN FRAMING AND BRICKWORK, WITCH SERVES BOTH AS INSULATOR AND FIRE-STOP



STANDARD CHIMNEY CONSTRUCTION

ELEVATION AND SECTION OF AN INTERIOR INDEPENDENT CHIMNEY SHOWING RECOMMENDED CONSTRUCTION.

FIG. NO. 3

FIG. #3. SHOWING SUPPORT OR FIRE-STOPPING AROUND CHIMNEY AND PROTECTING WOODWORK.



FIG. NO. 4

FIG. #4. STUD PARTITION ACROSS BACK OF FIREPLACE AND AROUND THE ENDS OF CHIMNEY BREAST, SHOWING PROPER METHOD OF ARRAINGING STUDS.

How to Lay Up Chimneys and Arrange the Floor and Roof Framing in Relation to Them to Make a Fire-Safe Structure.

DETAILS OF FIRE-RETARDING CONSTRUCTION



FIG. NO. 1 FIG. NO. 2

FIG. NO. 3

FIG NO. 1-2+3 SHOWING METHODS OF PROTECTING CEILING OVER FURNACE OR BOILER



FIG. NO. 6


TIN COVERING ON INSIDE FACE OF STUDS
INCOMB. MATERIAL PACKED IN AT FLOOR LEVELS
FLOOR JOIST
INSIDE FACE OF JOISTS COVERED WITH TIN.
DOUBLE PIPE.
SHEET METAL OR METAL LATHING NAILED ON INSIDE FACE OF STUD TO SUPPORT FIRE STOPPING.

FIG. NO. 7

FIG. NO. 6. - PROTECTION OF HOT AIR PIPE IN WOODEN STUD PARTITION.

FIG. NO. 7. ISOMETRIC SKETCH SHOWING METHOD OF FIRE STOPPING BETWEEN FLOOR JOISTS AROUND HOT AIR PIPE. CARRIED UP IN A PARTITION



FIG. NO. 4.

FIG. NO. 4. - SHOWING SECTION VIEW OF PROTECTION AROUND A SMOKE PIPE PASSING THRU A WOODEN PARTITION.



FIG. NO. 5.

FIG NO. 5 SHOWING ELEVATION OF FIG. NO. 4.



FIG. NO. 8

FIG. 8. SHOWING PROTECTION OF PIPE OPENING THRU FLOOR OR PARTITION.



FIG. NO. 9

FIG. NO 9 SHOWING A COMPLETE METHOD OF FIRE STOPPING, FLOOR REGISTER. WELL SUITED FOR EXISTING BUILDINGS.

Details of Fire Guards to Build in Around Heating Plant Pipes for Protection

DETAILS OF FIRE RETARDING CONSTRUCTION


FIG. 1
CONNECTION OF FLOOR JOISTS WITH OUTSIDE "BALLOON" FRAME AT PLATE LEVEL, SHOWING "BOX" CORNICE, GUTTER TROUGH, AND FOOT OF RAFTERS, AND METHOD OF FIRE-STOPPING.
RAFTER
MINERAL WOOL
MAIN PLATE
FLOOR JOIST
MINERAL WOOL
BOARD TO HOLD FIRE STOPPING
RIBBON GIRT
STUD.
FIG. 5
CONNECTION OF FLOOR JOISTS WITH OUTSIDE "BALLOON" FRAME. METHOD OF FIRE-STOPPING CORNICE AND "GAMBREL" ROOF CONSTRUCTION
RAFTER
MINERAL WOOL
MAIN PLATE
FLOOR JOIST
MINERAL WOOL
RIBBON GIRT
FIG. 2
SECTION THRU HEAD OF SLIDING DOOR POCKET IN A STUD PARTITION, SHOWING METHOD OF FIRE-STOPPING.
STUD
STUD
LATH AND PLASTER
FIG. 6
SECTION THRU FLUSH FRAME WITH PORCH CEILING JOISTS FINISHING AGAINST IT, AND METHOD OF FIRE-STOPPING
OUTSIDE FRAMING
MINERAL WOOL
FLOOR JOIST
PORCH CEILING JOISTS
FIG. 3
SECTION THRU POCKET AT FLOOR
DOOR
1/4" ASBESTOS BOARD
WOOD BASE
TOP OF FLOOR JOIST
FIG. 7
SECTION THRU AN OUTSIDE FRAME OVERHANGING AT SECOND FLOOR LEVEL, WITH CEILING JOISTS AND RAFTERS OF A PIAZZA FRAMED IN TO IT METHOD OF FIRE STOPPING OVER CEILING JOIST, ALSO FOR OUTSIDE OF FRAME WALL UNDER PORCH ROOF.
PORCH RAFTER
OUTSIDE FRAME
ASBESTOS OR SHEET METAL
MINERAL WOOL
1X2 NAILING PCS.
FLOOR JOIST
STUD
STUD
1/4 ASBESTOS BOARD OR 1/2" PLASTER
FIG. 4
SECTION PLAN THRU POCKET.

Details of Fire Retarding Timber Construction, Showing How to Do It the Better Way.

DETAILS OF FIRE RETARDING CONSTRUCTION



FIG 1

DIAGRAM SHOWING PLACING OF FLOOR BEAMS IN A WALL TO SECURE A SEPARATION OF AT LEAST 6" BETWEEN ENDS



FIG. 2

METHOD FOR BUILDING TWO FIRE PLACES BACK TO BACK IN A BRICK PARTY WALL TO SECURE SPACE BETWEEN ENDS OF JOISTS.



FIG. 3. FIG. 4.

FIG. 3 AND 4 - ELEVATION AND SECTION OF WOODEN CORNICE ON A BRICK WALL. NOTE SEPARATION OF CORNICE ON LINE OF PARTY WALL.



FIG. 5

SAME AS FIG. 7 EXCEPT THAT ATTIC FLOOR JOISTS ARE ANY DISTANCE BELOW THE PLATE AND BUILT INTO THE WALL SUPPORT FOR FIRE-STOPPING MIGHT BE SAME AS IN FIG 7

FIG. 6

FIRE-STOPPING AT A FLOOR LEVEL WHEN THE WALL IS THINNER ABOVE THE FLOOR THAN BELOW



FIG. 7

METHOD OF FIRE-STOPPING AT EAVES WHEN ATTIC FLOOR JOISTS ARE LEVEL WITH PLATE

FIG. 8

IN THIS AND THE OTHER FIGURES OF THIS PLATE NOTE FIRE-STOPPING OF WOODEN FURRING BY TWO COURSES OF BRICK WORK BEING SET OUT TO FACE OF FURRING, ABOVE AND BELOW FLOOR JOISTS ALL AROUND THE BUILDING OTHER TYPES OF MASONRY WALLS SHOULD BE BUILT OUT IN THE SAME MANNER

Details of Brick Walls with Mineral Wool Filler at Eaves and Floors; Also Double Fireplace Detail.



Details of Brick Veneer Construction—Four-Inch Face Brick Bonded to Wood Sheathing at Every Joist by Means of Metal Ties in Each Fourth Mortar Joint.



ISOMETRIC VIEW SHOWING BRICK VENEER CONST.



CELLAR SASH DETAIL



CASEMENT SASH DETAIL



WINDOW DETAIL



DOOR DETAIL



WALL SECTION OF BRICK VENEER BUILDING.

Details of Wall Construction, Including Window and Door Details of Face Brick Veneer Over Braced Wood Frame Without Sheathing. The Least Expensive Face Brick Construction for Residences and Other Small Buildings.



WALL SECTION OF BRICK BUILDING



ISOMETRIC VIEW OF SOLID BRICK WALL





CELLAR SASH DETAIL

CASEMENT SASH DETAIL



WINDOW DETAIL



DOOR DETAIL

Structural Details of the All-Brick Wall Type of Construction in Which a Masonry Bond Is Used Between the Face Brick Outer Courses and the Common Brick Backing.



Corner Bonding Detail for 8-Inch Walls of 8 by 5 by 12-Inch Hollow Tile.



Detail for Bonding Corners and Finishing Around Openings of 8-Inch Hollow Tile Walls with Common Brick.



Corner Bonding Detail for 5-Inch Walls by 8 by 5 by 12-Inch Hollow Tile.



Corner Bonding Detail for 5-Inch Walls of 4 by 5 by 12-Inch Hollow Tile Laid on the 5-Inch Bed. When Laid on the 4-Inch Face for 4-Inch Walls, the Corner Tile Would Be of 4 by 8-Inch Sections Cut to 4-Inch Length (4 by 8 by 4-Inch), Giving a 4-Inch Breaking of Joint.



Diagram Showing Placing of Opening in Hollow Tile Wall Having a 6-Inch Bond Between Courses.



Detail for Bonding Corners and Finishing Around Openings of 4-Inch Hollow Tile Walls with Common Brick.



Diagram Showing Placing of Opening in Hollow Tile Wall Having a 4-Inch Running Bond Between Courses.



Corner and Jamb Detail for 4-Inch Walls of 4 by 12 by 12-Inch Hollow Tile. Detail for Wall 3 by 12 by 12-Inch Hollow Tile Would Be Similar, Excepting That Corner Tile "X" Would Be Cut as Close to 9 Inches as Possible.



Section "A" for 8-Inch Walls of 8 by 5 by 12-Inch Tile; Section "B" for 4-Inch Walls of 4 by 5 by 12-Inch Tile and for Combining with Section "A" to Form Lintel for 12-Inch Wall Built of These Two Shapes. Similarly for 16-Inch Thick Wall Two Lintels of Section "A" Would Be Used.



Section "A" for 8-Inch Walls of 8 by 12 by 12-Inch Tile; Section "B" for 4-Inch Walls of 4 by 12 by 12-Inch Tile and for Combining with Section "A" to Form Lintel for 12-Inch Wall. Lintels Made of Single Blocks Similar to Section "A," but 10 and 12 Inches in Thickness, Are Used for 10 and 12-Inch Walls, Respectively. All Lintels for Section "A" Type for Fairly Wide Openings, Particularly for 10 and 12-Inch Walls, Should Have One or Both of the Cells "T" Filled with Concrete, Reinforced with a Light Rod or Heavy Wire to Prevent Breakage in Handling.





Joist Hangers May Be Used with Various Types of Lintels to Keep Head of Window Opening Close to the Ceiling Line.



Lintels for Structural Shapes. Section "A" for 8-Inch Walls of 8 by 5 by 12-Inch Tile; Section "B" for 8-Inch Walls of 8 by 12 by 12-Inch Tile. The Size and Weight of Steel Shapes Required by Any Span and Loading May Be Figured from the Carnegie or Other Structural Steel Handbook. These Lintels Should Usually Have 12-Inch Bearing.



Vertical Section of Wall of 8 by 5 by 12-Inch Load Bearing Tile Laid on the Side.



Vertical Section of Wall of 8 by 12 by 12-Inch Load Bearing Tile Set on End.


FINISH FLOOR
BUILDING PAPER
ROUGH FLOOR
2"x8" OR 2"x10" JOISTS SPACED 18" TO 24" ON CENTERS
10" TO 12"
1½"
LATH & PLASTER
12" TO 16"
1"x2" CROSS FURRING WHERE JOISTS ARE SPACED OVER 16" O.C.

Total Depth of Floor Construction Taken as 10 Inches Where 2 by 6-Inch Joists Are Used; as 12 Inches Where 2 by 8-Inch Joists Are Used, and as 14 Inches Where 2 by 10-Inch Joists Are Used. Actually the Thickness Will Often Average About 1 Inch Less Than These Figures, Which Will Allow for the Leveling Up of Any Irregular Joist, or the Cross Stripping of Underfloor, so That the Finished Floor May Run in the Same Direction as the Underfloor.



Section "A" for 8-Inch Walls of 8 by 12 by 12-Inch Tile; Section "B" for 4-Inch Walls of 4 by 12 by 12-Inch Tile and for Combining with Section "A" to Form Lintel for 12-Inch Wall. Lintels Made of Single Blocks Similar to Section "A" But 10 and 12 Inches in Thickness, Are Used for 10 and 12-Inch Walls, Respectively. All Lintels for Section "A" Type for Fairly Wide Openings, Particularly for 10 and 12-Inch Walls, Should Have One or Both of the Cells "T" Filled with Concrete, Reinforced with a Light Rod or Heavy Wire to Prevent Breakage in Handling.


TIE WIRES
WINDOW FRAME
YOKE OF 1"x3" STRIP WITH CROSS TIES OF SAME MATERIAL
TEMPORARY YOKE
TIE WIRE
STRIP OF TAR FELT PAPER
⅝"x1" TO 1½" STRIP PERMANENTLY NAILED ON TOP OF WINDOW FRAME
TEMPORARY STRUT WEDGED UP ON SILL

Details for Temporary Form Used for the Building of Lintels.



CORNER CONSTRUCTION
WITH COMMON OR FACE BRICK



SECTION





DETAIL OF WINDOW FRAME



Complete Construction Details of a 12-Inch Basement Tile Wall Using 8 by 5 by 12 and 4 by 5 by 12 Tile.



BASEMENT PLAN

FIRST FLOOR PLAN

SHOWING STEEL LUMBER LAYOUT FOR FIRE SAFE FIRST FLOOR.



SECTION-AA



SECTION-GG



SECTION-BB



SECTION-CC



ISOMETRIC DRAWING

Showing steel lumber floor construction.



SECTION-DD



SECTION-EE

Showing steel lumber framing around stair opening.



SECTION-FF



DETAIL

Showing partition running at right angle to Steel Lumber Joist.



ISOMETRIC DRAWING

Showing nailing strip notched out so that water pipes or wire conduits can be placed under wood floor into concrete slab.



ISOMETRIC DRAWING

Showing method used to suspend pipes from Steel lumber floor Joist.

Essentials of Steel Lumber Floor Construction as Used in Average Masonry Dwellings.



Floor Plans and Typical Details of Construction for Modern Display Windows for Stores.



By groups of four squares as a unit separated by wider joints, the scale is increased.



A diagonal pattern of square tiles is emphasized by a border.



By a few rows of broken joints, an effect of border is produced in a field of square tiles.



When the small squares are less than one-quarter of the area of the large squares, the pattern runs off at the side.



When the small squares are one quarter of the area of the large squares, the pattern has more repose.



By breaking joints in one course, the border is made wide.



An arrangement adapted to large rooms.



Another way to increase the scale with small tiles.



A decorative pattern that can be made on the job.



The simplest floor of square tiles is interesting if the joints are in scale.



When square tiles are laid with broken joints, long lines in one direction are the result.



When double squares are laid "basket pattern," the necessary allowance for joints adds interest.



A good pattern for corridors.



Varieties of "herringbone."



Two combinations suggesting plaids.



A simple device for a panel or a floor for a large room.

SUGGESTIVE PATTERNS FOR TILE FLOORS.







SKETCHES AT THE BUILDING.



LOOSENS WITH JARRING.
Is supported by the floor boards.
Sags and cracks the plastering

At the Left Is How Our Inspector Found the Work Being Done; at the Right the Better Way Is Shown.







FRAMING AS IT SHOULD HAVE BEEN.



THE OLD WAY OF MORTICING
or Preferable Dowel
JOIST HEADERS.

What Happens to Spiked Joists; Doweling Recommended.

GOOD AND BAD IN CARPENTRY WORK.



MATERIAL LIST

WALL BOARD

18 - 32"x84"	- 336	SQ FT
11 - 32"x108"	- 264	" "
1 - 48"x 96"	32	" "
4 - 48"x108"	144	" "
1 - 48"x120"	40	" "
	816	" "

SIZE. 22'-9" x 13'-10" x 9'-0"

MATERIAL LIST

TRIM

78 - LIN FT - 3" SPRUNG MOULD		
18 - Pcs $\frac{3}{8}$" x $2\frac{3}{4}$" - 9'-0" Long		BATTENS
4 - " " "	12'-0"	"
8 - " " "	14'-0"	"

This List does not include door or window trim nor baseboard



SECTION-A-A $\frac{1}{4}$ SIZE.



How to Figure on Wallboard Work. Plan A. See This Same Room Finished According to Plan B or C (Pages 28 and 29), Then Compare the Material List and You Will See the Difference in Cost on the Same Job When Different Trim Is Used.

MATERIAL LIST

WALL BOARD

11	32" x 84"	205 1/3	SQ FT
6	32" x 96"	128	" "
7	32" x 108"	168	" "
6	48" x 84"	168	" "
2	48" x 108"	72	" "
1	48" x 144"	48	" "
		789 1/3	SQ FT.







MATERIAL LIST

TRIM

WITH FLAT BEAMS

6 Pcs	7/8" x 3 1/2"	9'	282 Lineal feet
12 "	" "	12'	
6 "	" "	14'	

324 lin ft 1" x 1 1/8" Cove for ceiling
76 " " 3" sprung mould
40 " " 3/4" x 3 1/2" Border Mould
7 Pcs 5/8" x 2 1/2" - 16' long Wall batten.
444 lin ft 5/8" x 3/4" spec panel mould

All door & window trim and baseboard should be square edge material, no moulded edges

SIZE - 22'-9" x 13'-10" x 9'-0"



How to Figure on Wallboard Work. Plan B. This Is the Same as Shown in A and C (Pages 27 and 29). Note the Difference in Material Cost Thru the Use of Different Trim for the Same Job.

MATERIAL LIST

WALL BOARD

11- 32" x 84"	205 1/3	SQ FEET
6- 32" x 96"	128	" "
7- 32" x 108"	168	" "
6- 48" x 84"	168	" "
2- 48" x 108"	72	" "
1- 48" x 144"	48	" "
	789 1/3	SQ FT







MATERIAL LIST

TRIM

WITH BOX BEAM

76 Lin ft	Half-Beam	324- 7/8" x 4 1/2"
		124' 1 7/8" x 3 3/4" 343
124 " "	Full "	76' 1 7/8" x 1 7/8"
		124' 7/8" x 3 3/4"
		76' 7/8" x 1 7/8"

40 Lin ft 3/4" x 3 1/2" Border Mould

4- 5/8" x 2 1/2" x	12'	
2 " " "	14'	Wall Batten
7 " " "	16'	

444 lin ft 5/8" x 3/4" Spec. Panel Mould

SIZE- 22'-9" x 13'-10" x 9'-0"



DETAIL OF CEILING & WALL CONSTRUCTION

1/4 SIZE SCALE



How to Figure on Wallboard Work. Plan C. This Is a Further Illustration of the Room Shown in Plan A and B (Pages 27 and 28), But with a More Elaborate Panel Scheme. Note the Difference in the Material List on Trim as a Result.



PERSPECTIVE



DETAIL OF FLOWER BOX



SECTION THRU SEAT

SCALE 1½"=1'-0"



DETAIL OF WINDOW



END ELEVATION

SCALE ¼"=1'-0"



PLAN SCALE ⅛"=1'-0"

HOUSE INTERIORS. A SUN PORCH

Perspective Sketch, Elevation, Plan and Construction Details of a Sun Parlor Finished in Lattice Style Suggesting the Outdoors.



PERSPECTIVE



PLAN OF ALCOVE

SCALE 1/8" = 1'-0"

SCALE OF DETAILS = 3/4" TO 1'-0"



SECTION THRU SEAT



END ELEVATION



DETAIL OF CASE DOOR

SCALE 3/4" = 1'-0"



PLAN OF CASE, WINDOW + SEAT

SCALE 3/4" = 1'-0"



END ELEVATION

SCALE 1/4" = 1'-0"

ELEVATION

A LIVING ROOM ALCOVE

Architect's Sketch Showing Details of Living Room Alcove, Including Comfortable Upholstered Seat with Art Glass Windows Above. Bookcases and Fireplace in Tile with Bronze Hood.





Sketch, Plan, Elevations and Construction Details of an Attic Living Room.



PERSPECTIVE



PLAN
SCALE 1/8"=1'-0"



ELEVATION OF CASE SECTION
SCALE 3/4"=1'-0"



PLAN OF PYLON
SCALE 1"=1'-0"



DETAIL OF UPRIGHT
SCALE 1 1/2"=1'-0"



SECTION

SCALE 1/4"=1'-0"

ELEVATION

DETAILS OF A STAIRWAY

Perspective Sketch, Floor Plan and Details of Open Stairway Going Up Out of a Living Room. A Design of Considerable Originality.



A STAIRWAY WITH BOOK CASE

Perspective Sketch, Elevation, Plan and Scale Details of Semi-Open Stair Handled in the Modern Straight Line Style.



Sketch, Elevation, Plan and Details of Fireplace Alcove Suitable for Large Elaborate Living Room.



Sketch, Floor Plans, Elevations and Details of Interesting Dining Room Interior.



PERSPECTIVE



PLAN
SCALE 1/8" = 1'-0"



SECTION
SCALE 1/2" = 1'-0"



SECTION THRU TOP OF CASE
SCALE 3" = 1'-0"



PLAN
SCALE 1/2" = 1'-0"



SECTION
SCALE 3/8" = 1'-0"



ELEVATION OF BUFFET
SCALE 3/8" = 1'-0"

A KITCHEN CASE AND BUFFET

Details of a Commodious Cabinet and Sideboard to Be Built Into the Wall Between the Dining Room and the Kitchen.



PERSPECTIVE



PLAN



SECTION



DETAIL OF CASE BETWEEN WINDOWS.



ELEVATION OF INSIDE OF DOOR

- SECTION-THRU-CASE -
SCALE 3/4"=1-0



ELEVATION SCALE ¼"=1-0"



END

A SERVING PANTRY

Perspective Sketch, Plan and Details of a Well Equipped Serving Pantry.



Perspective Sketch and Working Drawing Showing Construction of an Ingenious Table Desk



Design and Details of Modern Style Stucco Porch.



Colonial Porch with Both Brick and Stave Columns.





Two Stair Designs.

Page 45 missing in original

Page 46 missing in original



How to Fasten Wood Rafters and Plate to Tile Wall, and How to Seat Joists on Tile.



Built-In Colonial Book Case—Recessed (See Opposite Page).



Arrangement of Book Case to Project Into Room (See Opposite Page).



·ELEVATION OF SIDE OF ROOM·



·ELEVATION OF END OF ROOM·

A LIVING ROOM WITH DETAILS OF INGLE AND STAIRWAY SCALE 1/4"-1'0"



·BACK OF SEAT·



·PLAN OF ROOM·

Living Room, with Ingle, Built-In Case and Stair (See Opposite Page for Details).



Details of Built-In Case, Seat, Etc., Used in Living Room Design on Opposite Page.



Built-In Wardrobe for Bedroom.



·ELEVATION·



·PLAN·



·SECT THRO· ·CUPBOARDS·

·SECT THRO· ·DRAWERS·

·A BUFFET· RECESSED IN A ·SMALL BAY· ·SCALE-¼" = 1 FOOT·

Side Board Set Into Wall.



·ELEVATION·



·SECTION·



·PLAN·

·TREATMENT· ·OF AN· ·INGLE NOOK· ·IN A· ·DINING ROOM· ·SCALE·¼"=1 FOOT·

Curved Ingle Nook with Open Shelves.

d as a Substitute for ..



Scale Drawings of China Closet Colonnade Between Dining and Living Rooms



A Built-in Side Board Novelty.





Trellis and Side Wall Ornament.



How to Build on a New Brick Porch, Showing Details of a Modernized Porch Suggested as a Substitute for the Old Porch



SIDE ELEVATION



FRONT ELEVATION



PLANS OF SIX ROOM ONE AND ONE HALF STORY RESIDENCE

SCALE ⅛" = ONE FOOT SHEET NO 1

Front and Side Elevations and Wall Section ⅛ Inch to the Foot of Pretty Little Six-Room Home.



SECOND FLOOR PLAN



FIRST FLOOR PLAN

PLANS OF SIX ROOM ONE AND ONE HALF STORY RESIDENCE

SCALE 1/8" = ONE FOOT SHEET NO. 2.

First and Second Floor Plans of Pretty Little Six-Room Home.





PLANS OF SIX ROOM ONE AND ONE HALF STORY RESIDENCE

SCALE ⅛" = ONE FOOT — SHEET NO 3.

Basement Plan and Section Thru Building Showing Construction ⅛ inch to the Foot of Pretty Little Six-Room Home.


2"X4" 16" O.C RAFTERS
BOARDS TO FORM CURVE
2"X4" 16" O.C. RAFTERS
ROOF SHEATHING
2 Pcs. 2"X4"
"X6" FLOOR
SHEATHING
2"X8" 16" O.C
2"X4" 16" O.C. JOISTS
1"X4"
LATH
PLASTER
1"X4" BEADED
BEV. SIDING
9'0"
2"X10" 16" O.C.
CONCRETE
"X8"
BRICK
SECTION THRU WALL & PORCH BOX
Scale 3/4" = 1'0"
2 PCS. 2"X12"
1"X6"
1"X8"
2'6"
1"X4" D.&M. BOARDS
GUTTER
BLOCK
MOULD
1"X10"
BLOCK
1"X12"
1"X6"
1'4"
5'0"
WOOD PANEL
WOOD DIVISIONS
D.S. GLASS
3'9"
BOOK CASE IN LIVING ROOM
Scale: 1/4" = 1'0"
1'6"
3 1/2"
WOOD
6'0"
10" PLT. MIRROR
GLASS
WOOD
2'4"
6"
END
BUFFET
Scale: 1/4" = 1'0"
18"
PLATE MIRROR
24"
MEDICINE CASE
1/4" = 1'0"
1 1/4" X 1 1/4 BALUST
5" SQUARE
SEAT
STAIR DETAIL
1/4" = 1'0"
1'4"
1'8"
D.S. GLASS
SHELVES
5'0"
PLASTER BACK OPEN
WOOD DOOR
DRWS
4'8"
9'0"
1'4"
3'0"
KITCHEN CASE
1/4" = 1'0"
PICT MOULD
CHAIR RAIL



LEFT SIDE ELEVATION





BASEMENT PLAN

PLANS OF A TWO STORY EIGHT ROOM RESIDENCE

SCALE 1/8" = 1'-0"

SHEET No 2.

Basement Plan and Details, ⅛-, ¼- and 1-Inch Scales, of Dutch Colonial Residence.





PLANS OF A TWO STORY EIGHT ROOM RESIDENCE.

SCALE 1/8" = 1'-0". SHEET No 3.

First and Second Floor Plan of Dutch Colonial Residence.



PLANS OF A TWO STORY EIGHT ROOM RESIDENCE

SCALE 1/8" = 1'-0"

SHEET No 4

Section and Construction Detail, Drawn to ⅛- and ½-Inch Scales, of Dutch Colonial Residence.



Typical Interior Details of Southern Style Residence.



Exterior Details of Construction, to Scale, of Southern Style Residence.



Complete Details of Interior Finish for Compact Residence.



Exterior Details of Construction, to Scale, of Compact Residence.

Built-in Furniture--Some Interesting Designs

ONE of the charms of the interior of any home is the furniture which is built into it. The dressers, seats, bookcases more than half solve the problem of furnishing it. Furniture that is built to fit the place it is in, is far more decorative and more comfortable than detached pieces could be in the same place. Not only is space saved by this means, but a keynote is given for the rest of the fittings in the home, which, unless it is utterly disregarded, will tend to keep the furnishings of the room in harmony.



Large Kitchen Cupboard, Lighted at Center by Casement Window.



Kitchen Cupboard of Generous Dimensions.



Dining Room Buffet.



Book Cases and Book Shelves.



Kitchen Dresser on One Side of Partition, Library Book Case on Other.



Details of Interior Finish of Brick and Stucco Finished Tile House



Exterior Details of Construction, to Scale, of Cement Plaster Residence.



Details of Interior Finish, to Scale for Cement Plaster Residence.











BUFFET DETAILS



·DINING·ROOM·BUFFET·



MEDICINE CASE







·PANTRY·DRAWER·CASE· ·MAIN·STAIR·DETAIL·

·INTERIOR·DETAIL·
·SHEET·NO·2·

SCALE
¼" & ⅜" = 1'-0"

Additional Details of Interior Finish, to Scale, for Cement Stucco Residence (See Pages 70 and 71).



SECTION OF PORCH & PART OF DINING ROOM

WINDOW SECTION



DETAIL OF PORCH ROOF



CORNER CONNECTION



CHEMICAL CLOSET

DETAILS FOR SUMMER COTTAGE



DETAIL OF BOTTOM RAIL



DETAIL OF TOP RAIL

Structural Details of Frame Cottage Representative of the Type of Construction Most Commonly Used in Frame Summer Cottages.



CONCRETE FOUNDATION FORMS

¾" EQUALS 1'-0"



CEMENT CHIMNEY CAP

SHOWING METHOD OF CASTING SAME IN PLACE



BELLY-ROD TRUSS

GIRDER FOR FRONT PORCH



FLITCH-PLATE GIRDER

CAN BE SUBSTITUTED FOR BELLY-ROD TRUSS GIRDER



TRUSSED GIRDER SCALE ⅜"-1 FOOT

CAN BE USED IN LIEU OF EITHER OF ABOVE GIRDER DESIGNS



BASEMENT POSTS



FOUNDATION WALL PLATES

SHEET of EXTERIOR DETAILS

SCALE ¾" & ⅜" = 1 FOOT

Construction Details of Prize Farm House.



ACCORDION DOORS
• 3/8" = 1'-0" •



SECTION
THRU ACCORDION DOOR
JAMB



SECTION
THRU ACCORDION DOOR
HEAD SHOWING OVERHEAD
TRACK CONSTRUCTION



BASE







PLATE RAIL
5½ FT. HIGH IN DIN. RM.



MEDICINE CASE



SIDE CASING



CHAIR RAIL



HEAD CASING



HALF ELEVATION of FIRE PLACE & SECTION
• SCALE 3/8" EQUALS 1'-0" •

▲ SHEET OF ▲
▲ INTERIOR DETAILS ▲
▲ SCALE 3/8" = 1' ¢ 1/2 FULL SIZE ▲

Interior Details of Prize Farm House.



SECTION THRU ROOF

SHOWING COMBINATION TILE AND REINFORCED CONCR. FLOOR AND ROOF CONSTRUCTION.

SECTION THRU FLOOR

SHOWING COMBINATION TILE AND REINFORCED CONCRETE FLOOR CONSTRUCTION.



SECTION THRU ROOF EAVE

FIRE-PROOF WALL FLOOR AND ROOF CONSTRUCTION

SCALE 3/8" = 1'-0"



WALL SECTION

SCALE 3/8" = 1'-0"


ASBESTOS SHINGLES
NOTE: ROOF BOARDS TO BE OF 1/8" × 3 1/4" MATCHED AND BEADED CEILING EXPOSED IN SUN PARLOR.
CUT RAFTER ENDS
SCREENS HINGED AT TOP.
SASH HINGED TO SWING IN AND PROVIDED WITH FASTENERS FOR HOLDING SAME WHEN OPEN OR CLOSED.
FLOWER BOX TIN OR COPPER LINED.
4"×4" BRACKETS
FLOOR
FLOOR JOIST
20"×8" CONC. FOOTING

SECTION THRU SUN PARLOR

SCALE 3/8" = 1'-0"



TILES FILLED WITH CONCRETE AND REINFORCED WITH 1/2" SQUARE BARS.

PROVIDE A BEARING OF AT LEAST 8" AT EACH LINTEL SUPPORT.

SECTION THRU ALL DOOR AND WINDOW LINTELS

SCALE 1 1/2" = 1'-0"

EXTERIOR WALL SECTION DETAILS

SCALE 3/8" & 1 1/2" = 1 FOOT

Construction Details of Hollow Tile Residence.



Details of Interior Finish in Modern Fireproof Residence.



A FOLDING BED IN DINING ROOM A SCALE 1" EQUALS 1'-0"



COOLER SECTION A KITCHEN A COOLER A SINK & CUPBOARD A ELEV A CUPBOARD SECTION



A LIVING ROOM BOOK CASE & FIRE PLACE A
A SCALE 1" EQUALS 1'-0" A

A SHEET A OF A DETAILS

A SCALE ¾" TO 1" EQUALS 1 FOOT A

Details of Interior Finish of Summer Bungalow.



Details of Construction of Summer Bungalow.



Details of Inside Trim and of Construction Used in Model Nine-Room Farm House.



Construction Details of Modern Farm House of Frame.



Detail of 1¾-Inch Double Door, Open In.



Detail of 1¾-Inch Double Door, Open Out.



Detail of 1¾-Inch Double Door, Open In, on Which the Narrowest Cylinder Front Door Lock Can be Used.



Detail of 1¾-Inch Double Door, Open Out, on Which the Narrowest Cylinder Front Door Lock Can be Used.



Detail of 1¾-Inch Double French Window, Open In, Bit Key or Thumb Bolt Lock.



Detail of 1¾-Inch Double French Window, Open Out, Bit Key or Thumb Bolt Lock.

Detail of 1¾-Inch Double Door on Which Regular 3½-Inch Inside Lock is Used.



Detail of 1¾-Inch Double French Window Having Rabbeted Lock, with Bit Key or Thumb Bolt.



Detail of 1¾-Inch Double French Win...



Detail of 1¾-Inch Double French Window, Open In.

STANDARD DETAILS FOR BUILDERS' HARDWARE.



Section Thru Meeting Rails of Pair of Inward Opening Casements. Note T-Astragal on Outside to Keep Out the Rain.



Section Thru Sill—Warranted Proof Even Against Driving Rain. Note That Standard Flush Bolt Requires Sill Rabbet to be at Least 5/8 Inch.



Section Thru Window Jamb, Flush with Plaster.



Section Thru Window Jamb—Use of 6-Inch Parliament Butts Permits Opening 180 Degrees.



Section Thru Recessed Jamb—Use of 6-Inch Parliament Butts Gives Room for Curtain Rod Brackets.

Details of Inward Opening Casements. All Details Half Full Size.

STANDARD DETAILS FOR BUILDERS' HARDWARE.



STANDARD DETAIL FOR OPEN OUT CASEMENT WINDOWS

"F," Section Thru Meeting Rails of Double Casements, Showing ⅜-Inch Rabbet to Fit Standard Mortise Turnbuckle. "G," Section Thru Jamb, Showing 1½ Inch Space Necessary for Standard Adjusters.



THE HARDWARE MAN'S FORM



DETAIL NO. 16. SIDEBOARD.



Diagram Illustrating Correct Detailing for Sideboard, and Hardware Trimmer's Short Hand Form for Listing Hardware Items.

STANDARD DETAILS FOR BUILDERS' HARDWARE.



Scale One-Half Full Size.

Detail of Single and Double Sliding Doors.

FOLDING DOORS.



Arrangement and Details of Doors to Fold into Flush Pockets.

STANDARD DETAILS FOR BUILDERS' HARDWARE.


SCALE 1/4" TO 12"
BOLTS TOP AND BOTTOM
STOP 1" WIDE ON TOP AND SIDE JAMBS.
4×4 BUTTS.
LEVER AND FLUSH CUP HANDLE.
DETAIL B.
SCALE 1" TO 12"

Arrangement for Accordion or Four Fold Doors Showing Only Proper Way.

Accordion Folding Doors

THERE is nothing in the building line which puzzles the millmen, the carpenter, and the hardware man so much as accordion folding partitions.

The manufacturers of accordion hangers should treat more fully on this subject. They should place in the hands of the architects full descriptive matter, also half size or full size drawings with hardware in place. Then the architects can show the carpenter how it is done and also show the hardware man what items he has to furnish to make a perfect workmanlike job.

Doors should never be made thinner than 1¾ inches, because a lock knob and flush cup handle cannot be applied in doors thinner than 1¾ inches.

The detail below shows six full width doors and two half width doors.

Here you have a sliding door proposition because the hanging of the doors forces you to it. You must supply a hanger for the door farthest from the half door, and a hanger for every second door from this.

You can readily see that the track is full width of the opening. You must use a sliding door lock with the regular flush cup escutcheons. You should use four flush extension bolts at the bottom. You cannot use flush bolts at the top because you cannot apply the strikes or keepers to the top jamb; *there is a slot in the top jamb.*

You can omit the use of the bottom bolts, but it is not good practice, because the doors will buckle and you have no other method of keeping the doors rigid at the bottom when same are closed.

If you wish to use eight full width doors and two half width doors you must use the same number of hangers as shown in the detail, but these two extra inner doors must be treated to operate same as regular pair of hinged doors with a soffit closing up the slot in the top jamb and bolts, lock, knob and flush cup handle.

Now, to obtain a good workmanlike job of folding partition doors, the writer suggests the use of the adjustable hanging strip as shown in detail to left.

If the doors shrink the flush bolts can be shot into their keepers. All makers of hardware furnish keepers or strikes with oblong holes in them (because they know doors will shrink), hence the strikes or keepers need not be moved.


ADJUSTABLE HANGING STRIP
CAN NOT USE LARGER THAN 4×3½" BUTTS ON 1¾" DOORS
NARROW FIRST DOOR.
SCALE ½ FULL SIZE.
4 FLUSH BOLTS AT BOTTOM—NO BOLTS AT TOP.
HANGERS
SLIDING DOOR LOCK AND CUP ESCUTCHEONS.
15' 0"
SCALE ¼" EQUALS 1'-0"

Half Size Detail of the Narrow Door Attached to Adjustable Hanging Strip.

Accordion Folding Doors — Directions for Ordering: Track Should be as Long as Opening is Wide. Brackets Should be Placed 2 to 2½ Feet Apart. One Hanger is Required for Every Other Door, Beginning with Door Farthest from Half Door. Doors Should Not Exceed 3 Feet in Width.



Detail of Double Doors to Open Out. Note That Edges Are Beveled, Not Rounded.



Detail of Double Doors to Open Out—for Schools, Churches, Theaters and Loft Buildings.



Plan View of Tracks for Four-Door School House Partition Heavy Enough to Carry Blackboard Panels; with Detail View of Pocket for Doors to Slide Back Into.

School-Room Partition Doors

ARRANGEMENT OF PARTITION DOORS HEAVY ENOUGH TO CARRY BLACKBOARD PANEL

WE show herewith, in the bottom detail, four sliding doors, all of which slide back into one pocket.

You will notice that this scheme is to take the place of accordion folding doors, dividing a large room into two or more smaller rooms.

This is especially desirable if these partition doors are required for additional blackboard space.

This device is in common use in the Chicago public schools, and is being installed in many of the schools in the larger cities. The accordion folding doors are much lower in price; but price does not count when a perfect up-to-date device is wanted.

Any number of doors can be used. If you have the space for a pocket in the opposite wall you can slide some of the doors into same.

If it is desired to hide these doors, a panel can be placed in front of the doors when same are back into the pocket.

This panel can be hung on invisible hinges and a very satisfactory job is obtained.



Detail of Outside Blinds for 10-Inch Wall. Note That There Must be a Space of at Least 2½ Inches Between Screen and Blind for Zimmerman or Gravity Fixtures; Scale One-Half Full Size.







Ornamental Gates and Fences.







Ornamental Gates and Fences.

Sun Parlor and Sleeping Porch Modernize Old Homes

THERE are few houses that were built before sun parlors and sleeping porches came into demand that cannot be remodeled so as to have these modern features. The cost of the additional rooms is more than gained by the satisfaction they give the owner and the increase in the value of the house, should it be sold.

In designing a sun parlor, or a sun parlor and sleeping porch, first consider the type of architecture of the house and place the addition where it will most improve the dwelling. The addition here shown was placed at the side of the house, at the front. This is constructed of face brick, set on a concrete foundation, with a stucco strip below the sleeping porch windows. Details of the construction are given in the section.

The floor plan of the sun parlor, or living porch, calls for a tile floor, but any material suitable or wanted by the owner can be substituted. The glazed doors leading from the living room to the porch also can be changed into any other desirable type, or left out altogether.

In this design the roof line was extended out over the porch to conform to that of the rest of the building. That is a feature that should not be overlooked—to so design and build the addition that it will not appear as an addition, but apparently will be a part of the original construction.

As has been said, this design is susceptible to many alterations. For instance, the living porch here shown can be transformed into an outdoor dining porch, adjoining the dining room, with a sleeping porch above. When such an addition is made, the construction will be more simple, as dining porches usually were merely screened in, being placed in a position where there is more privacy.



ELEVATION OF NEW LIVING PORCH

Showing How a Sun Parlor and Sleeping Porch Can be Added to Many Homes.



Perspective Sketch, Floor Plan and Details of an Artistic Sun Parlor or Conservatory Addition to be Built onto a Stucco House

NOTE: THIS TYPE OF GAS LOG FIREPLACE & BOOKCASE COMBINATION IS VERY MUCH USED IN APARTMENENT HOUSE CONSTRUCTION; FOR ECONOMY IN CONSTRUCTION IT CANNOT BE IMPROVED UPON FOR A LIVING ROOM FIXTURE IN MODERN APARTMENT HOUSES.



A PLAN VIEW A

A LOOKING DOWN ON BOOKCASES A FIREPLACE & HEARTH A



A SECTION A

A FRONT VIEW A

A OF LIVING ROOM BOOKCASES & A GAS LOG FIREPLACE A

A SCALE ⅜" EQUALS 1 FOOT A





ELEVATION



Details of Enclosed Porch and Separate Entry with French Doors and Cement Windows Between Porch and Living Room.



WROUGHT IRON DOORS FOR A CITY BANK



WROUGHT IRON DOORS FOR A CITY BANK



FIREPLACE CONSTRUCTION FOR A ONE OR TWO FAMILY HOUSE



STORE FRONT DETAILS

SCALE 1/2 & 1/4 FULL SIZE

MAIN WALL SECTION & PART ELEVATION

SCALE 3/8" EQUALS 1 FOOT

Show Window and Front Wall Construction of Store Building.



SECTION AND ELEVATION OF SHOE STORE SHELVING

SCALE $\frac{3}{8}$ INCH EQUALS ONE FOOT



SECTION AND ELEVATION OF DRUG STORE FIXTURES

SCALE $\frac{3}{8}$ INCH EQUALS ONE FOOT

Details of Shelves and Fixtures Suitable for Shoe Stores and Drug Stores. The Ladder Construction for Handling the Shoe Store Shelving Is a Feature. The Drug Store Design Is a Standard Design Such as Might Be Found in a Well Arranged Drug Store.



SECTION & ELEVATION OF DRY GOODS STORE FIXTURES

SCALE $\frac{3}{8}$ INCH EQUALS ONE FOOT



SECTION & ELEVATION OF HARDWARE STORE FIXTURES

SCALE $\frac{3}{8}$ INCH EQUALS ONE FOOT

Shelves and Fixture Arrangements for a Modern Dry Goods Store and a Hardware Store. The Small Labeled Drawers Are the Most Useful for a Hardware Store. The Broad Shelves for the Dry Goods Do Not Need to Be Marked as the Material Can Be Easily Seen.



Details of Interior Finish in Second and Third Floor Apartments.



Details of Special Interior Trim in Hall and in Living Quarters.



TRUSS SECTION

BOWSTRING LATTICE TRUSS

THIS STYLE OF TRUSS IS CONSIDERABLY STRONGER THAN THE ONE BELOW OWING TO THE CURVATURE OF THE TOP CHORD: BUT SOMEWHAT MORE COSTLY TO CONSTRUCT



METHOD OF REINFORCING TRUSSES

WHERE A BLOCK & TACKLE HOIST IS DESIRED: THIS METHOD DISTRIBUTES THE SUDDEN & CONCENTRATED LOAD OF LIFTING AUTOMOBILES, CASTINGS, ETC.



TYPICAL LATERAL TRUSS BRACE



TYPICAL FLAT ROOF WOOD LATTICE TRUSS



SECTION THRU TRUSS SHOWING DIFFFERENT HEIGHTS UNDER ROOF PITCH 3" TO EVERY 10 FEET.

Details of Two Styles of Lattice Truss Suitable for Public Garage 40 Feet in Width.


GRADE
TO TRUSS
13'-6"
FLOOR
LATERAL BRACES
1/2"x24" PLATE ANCHORS 6 FEET APART
8"x8" WALL PLATE
110'-0"
TAR & GRAVEL ROOF
GUTTER
DOWN SPOUT
NOTE: TRUSSES ARE SPACED 10 FEET ON CENTERS, BEARING ONTO 8"x8" CONTINUOUS WALL PLATES ANCHORED IN PLACE: TRUSSES HAVE LATERAL BRACES IN CENTER OF SPAN: SEE DETAIL DRAWINGS

LONGITUDINAL SECTION

SHOWING SPACING OF TRUSSES & LATERAL BRACES

Details of Public Garage.



Floor Plan of Garage Showing the Arrangement of the Various Parts. The Front of the Building Contains a Display Room for Accessories and Show Cars. Back of This is the Stock Room and Office Which Can be Easily Made Very Attractive From the Front. The Turntable in the Center Simplifies the Handling of Cars. There is a Commodious Shop at the Rear.


ELEVATION & PLAN VIEW SHOWING
CONSTRUCTION DETAILS OF A STEEL BOW-STRING TRUSS; THIS TYPE OF TRUSS ALTHO MORE COSTLY THAN WOOD HAS THE ADVANTAGE OVER THE LATTER IN STRENGTH AND FIRE RESISTING QUALITIES.
50'-0"
42 FT. RADIUS TO CENTER LINE
COMPOSITION ROOFING
2'-4" BRIDGING BETWEEN EACH SPAN OF ROOF JOISTS.
GUTTER
PILASTER
TOP CHORD 2-6"x4"x⅜" ANGLES
LOWER CHORD 2-4"x4"x⅜" ANGLES
½" THICK GUSSET PLATES
½" RIVETS
CENTER LINES
½" RIVETED JOINTS
2-5"x3"x⅜" ANGLES
2-5"x3"x½" ANGLES
2'-8" ROOF JOIST 20" ON CENTERS
13" THICK BRICK WALL
4'-2" PILASTER PROJECTIONS UNDER EACH TRUSS
16'-24'-1" STEEL BEARING PLATES FOR ALL TRUSS SUPPORTS.
DETAIL OF COMBINATION TILE & REINFORCED CONCRETE FLOOR OVER BOILER & FUEL ROOM, FIGURED TO CARRY A SAFE LOAD OF 250 LBS. PER SQ. FT. WITH ½" SQ. REINFORCING BARS.
½" BARS SPACED 12" ON CENTERS ON TOP
¾" BARS SPACED 6" ON CENTERS
DETAIL OF SOLID REINFORCED CONCRETE FLOOR SLAB OVER BOILER & FUEL ROOM; WITH THE USE OF BEAMS AT 13 FT. INTERVALS THICKNESS OF SLAB COULD BE REDUCED TO 5". SLAB FIGURED TO CARRY 250 LBS. PER SQ. FT.
COMPOSITION ROOFING
1'-6" MATCHED ROOF BOARDS
2'-8" ROOF JOISTS 20" O.C.
2'-6" PLATE BOLTED TO TOP CHORD
½" STEEL BRACING RODS
TURNBUCKLES
8'-0"
16'-0"
DETAIL SHOWING METHOD OF BRACING.
ANGLE IRONS CAN ALSO BE USED FOR THIS PURPOSE.
DETAIL SHOWING METHOD OF HOLDING ROOF JOISTS IN PLACE BY MEANS OF 3"x3"x¼" ANGLE CLIPS
ANGLE CLIPS BOLTED TO TOP CHORD
DETAIL SHOWING METHOD OF HOLDING ROOF JOISTS IN PLACE BY MEANS OF 4"x4"x⅜" WOOD ANGLE BLOCKS.
WOOD BLOCKS ON TOP CHORD
2'-8"

Details of Light Steel Truss for 50-Foot Span Curving Roof Garage, Also of Concrete Floor Over Heating Room in Public Garage.


6" THICK FLOOR SLABS REINFORCED WITH 1/2" TWISTED BARS LAID 12" & 4' ON CENTERS RESPECTIVELY.
STIRRUPS
1" TW. BARS
ALL CORNERS & EDGES CHAMFERED
3/4" TWISTED BARS
1/4" SPIRAL REINFORCEMENT IS HELD IN PLACE BY 3 SPACERS BETWEEN EIGHT 1" RODS.
PLAN VIEW SHOWING COLUMN REINFORCEMENT.
4'-0"
9"
1/2" TW. TOP BARS 12" O.C.
1/2" BARS 5" O.C.
1/2" BARS 8" O.C.
TOP BARS 1/2" TW. 12" O.C.
12" BRICK WALL
6"
TYPICAL REINFORCED CONCR
STAIRWAY DETAIL; TO BE CAST IN CONJUNCTION WITH FLOOR SLABS AND NOT SEPARATE
SCALE 3/8" EQUALS 1 FOOT
TYPICAL FLOOR & COL. REINF.
SCALE 3/8" EQUALS 1 FOOT
WHITE ENAMEL TERRA COTTA COPING.
GREEN T.C.
WHITE T.C.
BRICK 1" PROJECTION
NOTE: ROOF SLAB PITCHES 18 INCHES FROM FRONT & REAR TO DOWN SPOUT AT CENTER OF BUILDING.
TAR & GRAVEL ROOF
FLASHING BLOCK
PIVOTED VENTILATING SASH
STEEL SASH
PIVOTED SASH
13'-0"
1'-8"
BRICK
BRICK 1" PROJ.
6" THICK REINF CONCRETE FLOOR SLABS
7'-0"
14'-0"
NOTE: PILASTERS PROJECT 9"
CENTER LINE
13'-6"
2'-0"
4"x4" T.C. BLOCK 1" PR.
NOTE: ENTIRE FRONT FACED WITH RED FACE BRICK.
WHITE ENAMEL TERRA COTTA
PLATE GLASS
BRICK ROWLOCK
BLUE GRANITE TERRA COTTA
SIDEWALK LEVEL
6" THICK REINFORCED CONC. FL. SLAB (SEE DET)
8'-6"
3'-6"
2'-0"
8 FT. SQ. REINF. CONC. FTG.
HALF FRONT ELEVATION
HALF CROSS SECTION
SCALE 1/8 INCH EQUALS ONE FOOT

Details of Reinforced Concrete Factory Building. Reinforcing of Floors, Girders, and Columns Are Shown and Also Arrangement of Exterior Finish.



REINFORCED CONC. STAIR DETAIL



INTERSECTION OF COLUMN, GIRDER & BEAM



HALF CROSS SECTION

HALF FRONT ELEVATION

Working Details Standard Mill Construction Factory Building.



Details of Construction of Modern Photo Play House.



SECOND FLOOR PLAN
$\frac{1}{8}$" SCALE


3" BRICK WALL
TOP REINF. ¼" TW BARS 12" C.C.
¼" × 8" PLATE
5" - 9¾ LB. I BEAM
BOTTOM REINF ½" TW BARS 6" C.C.
2 - ¾" REINF BARS
10'-6"
8'-2"
6" - 12¼ LB. I BEAM.
15" I BEAM 42 LBS ¢
10" × ¼" PLATE
TOP REINFORCEMENT ¼" TW BARS 12" C.C.
¼" × 8" PLATE RIV. TO TOP OF 6" I BEAM.
BOTTOM. REINF. ½" TW BARS 6" C.C.
6" I BEAM COLUMN.

SECTION THRU OPERATOR'S R.M.
SHOWING METHOD OF CONSTRUCTING A FIRE-PROOF MOVING PICTURE MACHINE OPERATOR'S COMPARTMENT



TRUSS SECTION
$\frac{3}{4}$" SCALE

CROSS SECTION — HALF FRONT ELEVATION
SCALE $\frac{1}{8}$ INCH EQUALS ONE FOOT

Details of Construction of One-Story Theater. An Up-to-Date Business Attracting Front is Provided and the Operator's Room is of Fireproof Construction.



HALF SECTION



STORE FRONT SECTION

Details of Construction and Finish of Stores with Lodge Hall Above.



Design and Arrangement for Model Ice House.



Design and Details of Simple Farm Ice House.



SECTION A-A



SECTION B-B



CONSTRUCTION OF CEILINGS



CONSTRUCTION OF FLOORS



CROSS SECTION

Details of Construction of Community Cold Storage Plant and Ice House, Showing Special Insulation.



CROSS SECTION OF POULTRY HOUSE



Cross-Section of Lumber Yard Shed, Showing Approved Method of Construction.



TROUGH SECTION FRONT VIEW of TROUGH

TROUGH & PEN ENCLOSURE



REMOVABLE PLANK FLOORS



DETAIL of SMALL DOORS



IMPROVED WINDOW DETAIL



WOOD TROUGH.



GUARD RAIL DETAIL



HOG HOUSE SECTION AND DETAILS

SCALE ¼" + ⅜" = 1'-0"

Details of Winter Hog House of Modified Saw-Tooth Roof Type. Face This Building Toward the South, and It Will be Warm and Well Lighted All Winter.



FRONT ELEVATION



FRONT PANEL SECTION.



END ELEVATION



CROSS SECTION.
1/4" = 1'-0"

COMMUNITY HOG HOUSE WITH CONCRETE YARDS.

Working Drawings of Community Hog House Design. Elevations Drawn to Scale ⅛ Inch Equals One Foot. Cross Section Detail, ¼ Inch Equals One Foot.

Bank Building and Lodge Hall

SINCE the building which is to contain a banking business and lodge hall is sure to become the center of business and social activities among the men in the community in which it is erected such a building should be somewhat out of the class of commonplace structures. Good substantial construction to which is added the necessary artistic treatment required to place it in somewhat of a class by itself are the most important of the several factors to be considered in the design of such a building. The finish of the exterior may be made very impressive by the use of ornamental face brick with terra cotta trim. The use of these materials has come to be standard in city construction and there is nothing which impresses the stranger with the progressiveness of a town more than to see the business section being built up with structures in which these modern materials are used.

The building illustrated here occupies a corner lot and is 30 by 50 feet. The entire first floor is designed as a bank and the second floor is taken up by the lodge hall. The ornamental front is placed on the 30-foot side of the building. The portions of the front wall above the first floor windows and between the sets of second floor windows are finished with face brick while the entrance, columns and entabulature are built of terra cotta. The small-paned windows add a great deal to the distinctive appearance of the building. There is a sufficiently elaborate treatment given all of the details to mark this building as one of importance among the various structures along the street upon which it would be placed.

The heavy brass trimmed door of the bank opens into a small vestibule in which there are entrance and exit doors connecting with the main corridor. At the right upon entering is a private office having doors both into the public square and into the banking space. Three cages are placed facing the side wall of the building and bounding the main corridor near the front of the bank. These cages are built up of wood panels from the floor to the counter, which extends from the private office along the side of the first cage and along the front of the three cages down the corridor. Above the counter there is a bronze grillwork on the outside of the cages and steel lattice partitions are used between cages.



First Floor Plan. **Second Floor Plan.**

Arrangement of Bank Building.



Front Elevation of Cashier's Cage and Trim Details in Bank Building.



Details of Terra Cotta Ornamentation on Exterior of Bank Building.



FRAMING OF JOISTS OVER DRIVE WAY



DETAIL OF GUARD



SECTION OF DOWN SPOUT



CROSS SECTION



SECTION



PLAN

GRANARY DETAILS

SCALES $\frac{1}{8}$", $\frac{1}{4}$" & $\frac{3}{8}$" = 1'-0"

Construction Details of Two-Story Gambrel Roof Corn Crib and Granary.



Details of Construction of Two-Story Gable Roof Combined Corn Crib and Granary.



Details of Construction of C0-Foot Diameter Barn with Central Silo.



Details of Gothic or Curving Roof Barn.



DETAIL OF HAY CARRIER TRACK



DETAIL OF POST AND PURLIN INTERSECTIONS



PURLIN SPLICE



SECTION THRU COW BARN



6" WROUGHT IRON COLUMN DETAIL

SHEET OF COW BARN DETAILS

SCALE
⅛"-¾" & 1½"-1 FOOT

Heavy Timber Framing Details for Remodeled Dairy Barn.



Details of Horse Barn. Roof Is Self-Supporting Plank Frame Construction of the Type Where Every Rafter Forms a Truss. Rafters Spaced on 24-Inch Centers.



CORNER POST DETAILS



BARN DOOR DETAILS







SASH STOP AND SHIELD DETAIL



HORSE STALL DETAIL



STUDDING SOCKET DETAIL

SHEET of HORSE BARN DETAILS

SCALES
1½" & ⅜" EQUALS 1 FOOT

Working Details of Construction and Special Equipment for Horse Barn.



Details of Construction Drawn to Exact Scale of Gambrel Roof Barn with Dormers.



DETAIL OF HORSE STALL PARTITIONS



CORNER POST DETAILS



BARN DOOR DETAILS



CROSS SECTION SCALE ⅛"=1'-0"



SECTION 'A-A'



SECTION AT SILL
SCALE ½" = 1'-0"

SHEET OF BARN DETAILS

Construction Details of Small Farm Barn with Self-Supporting Gambrel Roof.



ELEVATION OF HARNESS CABINET

SCALE $\frac{3}{8}$" = 1'-0"

SECTION



CROSS SECTION

SCALE $\frac{1}{4}$" = 1'-0"



SECTION THRU FLOOR

SCALE $\frac{3}{8}$" = 1'-0"

Cross-Section Thru Self-Supporting Gambrel Roof of Barn, Showing Also End Framing. Roof Trusses Are Spaced About 12 Feet Apart.



DETAIL AT SILL



WINDOW HEAD



JAMB

SCALE 1½"=1'0"



FRONT ELEVATION

SECTION & SIDE ELEVATION

SCALE ⅜"=1'0"

HORSE STALL DETAILS

Details of Horse Stable Part of Combination Barn. Note Improved Stall Flooring of Creosoted Blocks Laid on the Concrete. Plank Frame Construction at Sill Also Clearly Shown.



SHEET OF BARN FRAMING DETAILS

Detail of Gambrel Roof Horse Barn, Showing End Framing, and Also Intermediate Plank Frame Truss. Sketches Above Show Clearly the Principal Connections in This Type of Truss.

NOTE:- THIS TYPE OF TRUSS CAN BE SPACED FROM 10 TO 14 FT. ON CENTERS.



SIDE FRAMING OF TWO STORY BARN

SCALE 1/8"=1'-0"

Side Framing Detail of Gambrel Roof Horse and Storage Barn. Note That Plank Frame Trusses Are Set from 10 to 14 Feet Apart to Work Out Right with the Floor Plan.



Cross-Section Thru Gambrel Roof Barn. This Is an Example of Radford's Standardized Plank Frame Construction, Making Use of 2-Inch Plank Carried Regularly in Stock at All Lumber Yards.



Longitudinal Section Thru Big Gambrel Roof Barn. This View Shows Intersection of Horse Stable Wing with Main Section. Notice How Passageway in Hay Mow is Formed Across th Center of the Barn to Make All Parts of the Mow Accessible, Even When the Center is Filled.



Details of Sanitary Cow Stalls and Horse Stalls in Big Barn.



Cross-Section Thru Beef Cattle Barn, Showing Detail of Plank Frame Construction. Trusses Spaced 12 Feet Apart.

STOCK BARN SECTION



Stable Floor Plan of Beef Cattle Barn. There Is a Series of Stock Pens Along Barnyard Side, Each Pen Just Large Enough to Hold a Double Row of Steers at the Feed Mangers. Overhead Feed Carrier Service Runs Along Main Driveway and Into Each Feed Ally. Portable Gates in Covered Barnyard Separate the Stock Into Groups as Desired.



HAY CHUTE AND MANGER



STOCK BARN FRAMING ELEVATION



TRUSS DETAIL

STOCK FEEDING BARN DETAILS

SCALE: ⅛" & ¼" = 1 FT

Details of Plank Frame Construction for Beef Cattle Barn. These Trusses Are Built Up of 2-Inch Planks and Are Spaced 12 Feet Apart.



ELEVATION of BOX STALLS





WINDOW HEAD



JAMB

WINDOW SILL



ELEVATION of STOCK PEN AND DETAILS IN STOCK BARN A

SCALES ⅜" & ¾" = 1'-0"

Details of Stock Pens, Etc., for Beef Cattle Barn.



Cross-Section of Community Hog House Showing Construction.



CROSS SECTION OF SELF FEEDER



FRAMING PLAN OF SELF FEEDER

Details of Large Self-Feeder for Cattle.





Working Details of Dairy Stable Basement for Remodeled Cow Barn.



Details of Heavy Timber Framing for Stock Barn.



Details of Gable Roof Dairy Stable. Span of Roof 32 Feet. Concrete Foundation Walls Extend Up 3 Feet 10 Inches. Above This the Inside Is Lined with Wall Board, for Both Side Walls and Ceiling.



CROSS SECTION
THRU FLOOR



DETAIL OF BRIDGING



DETAIL OF FOUL AIR SHAFT.



ELEVATION OF PIPE PANELS



SILO ROOF DETAIL

Details of Dairy Stable. Note How Cow Stalls Are Floored with Cork Brick. Cow Stall Partitions and Pens of Metal Piping Also Specified. Note Improved Silo Roof Details, Which Shows How to Put on an Extension Metal Roof.

BARN DETAILS

SCALE $\frac{1}{8}$" + $\frac{3}{8}$" = 1'-0"



CONCRETE FOUNDATION FORMS

SCALE $\frac{3}{8}$" = 1'-0"

CROSS SECTION

SCALE $\frac{1}{8}$" = 1'-0"

Details of Construction of Monitor Roof Stock Barn.



Section Thru Hollow Tile Horse and Cow Barn, Showing Framing for Self-Supporting Roof. The Tile Walls Extend Clear Up to the Eaves. The Purlin Braces Come Down to the Floor Joists and Are Tied to the Ends of the Truss Chord Above at the Plate Line by Means of Two Pieces of 2 by 12 for Each Truss. This Takes the Outward Thrust Away from the Top of the Tile Wall.



Working Drawings of Handy Cart for Feeding Silage. The Cart Runs on a Light Angle-Iron Track the Length of the Feed Alley. It Is Filled Directly from the Silo, and When the End Gate Is Opened the Silage Is Raked Out and Distributed with a Minimum of Time and Labor.



CROSS SECTION

Dimensioned Construction View of Scale House.



SECTION THRU CORN CRIB

Small Single Corn Crib of the Good Old-Fashioned Type Resting on Concrete Posts 12 Inches Above Ground to Keep Out the Rats and Mice. The Building Is 4 Feet Wide at the Base, Sloping Outward to a 6-Foot Width at the Plates. The Height Is 11½ Feet and the Length 16 Feet; 1 by 4-Inch Battens Placed 1 Inch Apart Form the Sloping Side Walls and Assure Plenty of Ventilation. For Convenience in Filling, There Are Two Small Doors High Up in the Side. A Good, Tight, Well Framed Roof Is Provided, Making This a Very Secure Corn Crib.



Cross-Section of Fireproof Dairy Stable of Reinforced Concrete, Showing Some of the Construction Features. The Air Intake Is Built Thru the Ceiling Over the Stable, Which Is of Concrete and Tile. The Truss Framing for the Roof Is Unusual.



CROSS SECTION OF CORN CRIB

Details of Construction of High Corn Crib and Granary. Note How the Distributing Hopper Is Arranged in the Cupola.



Ground Floor Plan.

Upper Floor Plan.



CROSS SECTION

Cross-Section Thru Combined Corn Crib, Grain House and Implement Storage Shed.

Roof Truss for 36-Foot Barn

Question—Would plank frame construction be heavy enough for a barn 36 feet wide, or would it be advisable to use another form of truss? What size plank should be used in a barn 36 feet wide, using 18-foot studding, 2 by 6's? There will be 2 by 6 rafters, two 2 by 6's for plates, 4 by 6's for sills, 2 by 10's for joists, and two 2 by 12's for girders, with 4 by 6 supports placed 9 feet apart. The joists would be 16 feet long between wall and girder.

Would you advise tying with a 2 by 6 at a point just below the plate to the floor joists, say at an angle of 45 deg.? The braces on the rafters are to be 1 by 8's.

Answer—If you will cover the joints of the intersecting rafters with 1 by 8-inch cleats on each side, it will strengthen this point very much (see detail at section A-A). The 1 by 8-inch braces on each side of the rafters are heavy enough for a barn of ordinary construction, if it is not exposed too much to high wind.

For a barn with 18-foot studding use 2 by 6-inch timbers instead of 1 by 8-inch for the lower brace.

If the barn is exposed to high winds, we would advise tying with a 2 by 6-inch at the point just below the floor joists, spaced 8 feet on centers.

In regard to the floor joists, 2 by 10-inch are not heavy enough for a span of 16 feet with the amount of hay storage that you have to carry. We would recommend using 2 by 12-inch joists and spacing the posts 11 feet 6 inches from the outside wall. This would make the span more evenly spaced.



Detail Showing Recommended Sizes for Various Members in Plank Frame Barn That Is 36 Feet Wide.


Plans of George Lake Culvert Twp. Rascoe 1916.
R.R. Carter Highway Engineer.
To be constructed in accordance with the State of Illinois State Highway Dept. Contract Form and General Specifications for Bridge Work, Edition of July, 1915.
All exposed edges to be beveled with a ¾" triangular molding.
Class 'A' concrete to be used throughout
Proportions 1-2½-4.
All steel reinforcing bars must be mild or medium steel rolled from new billets. No rerolled material or high carbon steel will be permitted.
All bars must be obtained in the full lengths indicated in bill of material
B.M. Two spikes in oak tree at ditch, W side of road - El. 91.25
Plan
Elevation Showing Reinforcing
End View of Drop
End View Down Stream
Bill of Material
Letter | No. | Size | Length
a | 134 | ½" sq. | 5'-0"
b | 8 | ⅜" sq. | 19'-6"
b1 | 8 | " | 15'-9"
h | 12 | " | 17'-0"
h1 | 7 | " | 5'-0"
U | 5 | " | 14'-0"
m | 4 | " | 4'-0"
V | 58 | " | 3'-9"
V1 | 14 | " | 5'-6"
V2 | 4 | " | 6'-6"
Wrought Iron Pipe | 1½" | " | 32'-0"
Steel 1013 #
Concrete 14.5 Cu yds.
El. Flow Line 840
El. Gutter 93.5
Grade El. 92.5
Flow Line
12'-0" Roadway
27'-10"
37'-6"
8'-6"
6'-0"
3'-0"
1½" W.I. Pipe

DESIGN AND CONSTRUCTION OF SPECIAL HIGHWAY DRAINAGE STRUCTURES.

Detail Illustrating a Type of Box Culvert Used to Drop Elevation of Water Flow Line Without Scouring of Soil.







Note - Culverts having spans of 4'-0" or less may be constructed without wingwall footings if (b) bars are placed 1½" from outer face of sidewalls and bent 18" into headwalls, 1½" from outer face. (h) bars are also moved to outer face of sidewalls. Distance "B" should be 12" on up-stream and 2'-6" on down-stream end, measured from bottom of pavement with footing omitted.

In culverts of span 4'-0" or under, 2-(h) bars are placed 4" from top of headwall, 2" from either face and (b1) bars are bent into center of wall.

All steel should be mild or medium first grade stock. Lengths not indicated should be figured with the end clearances shown in the diagram and should be obtained in the full lengths indicated or calculated.

Bevel all exposed edges with ¾" triangular moulding.

Length L as calculated from the equation given below implies a slope of 1½ to 1 for earth fill falling around ends of headwalls.

Dimensions shown are not intended to apply to culverts carrying heavy fills. Culverts of span 4'-0" or under will carry fill of 4'-0"; all others are designed to carry fill of 1'-0" only. Concrete should be proportioned 1-2½-4 thruout.

C = 0.4(H+T)

L = 1.5(H+T+F)

| Dimensional Data | | | | | | | Reinforcing Bars | | | | | | |


Plans of Brandt Bridge Roscoe Twp. 1916
Bill of Material
Letter | No. | Size | Length
V | 36 | ¾" | 5'-0"
Vi | 28 | ½" | 9'-0"
h | 12 | ⅜" | 21'-0"
h1 | 24 | " | 9'-0"
a1 | 47 | ¾" | 28'-0"
a2 | 15 | " | 29'-6"
a0 | 86 | " | 7'-0"
b1 | 25 | ⅝" | 23'-0"
b | 33 | " | 19'-0"
t | 24 | ½" | 3'-9"
m | 13 | " | 4'-0"
Steel 5735#
Concrete 50.3 cu yds
To be constructed in accordance with the State of Illinois State Highway Dept. Contract Form and General Specifications for Bridge Work Edition of July, 1915.
All exposed edges to be beveled with a ¾ triangular molding.
Where grooved panels are shown the same to be made with ½ triangular molding.
Place 3" tile drains in side walls about 18" above pavement. Bk. cts.
Class "A" concrete to be used throughout.
Proportions 1-2½-4.
All steel reinforcing bars must be mild or medium steel rolled from new billets
No rerolled material or high carbon steel will be permitted.
All bars must be obtained in the full lengths indicated in bill of material.
B.M. - Two spikes in corner post, W. side of road, S side of road.
End Elevation
General Elevation
End of Wing
Side Elevation
Section S-S
Plan
Grade El. 100.5
3" tile drains
Bed of Stream

DESIGN AND CONSTRUCTION OF SPECIAL HIGHWAY DRAINAGE STRUCTURES.

Double Box Culvert Designed to Reduce the Cost of a Long Span Necessary Because of Limited Vertical Clearance.


Section A-A
Section B-B
Section CC
Section DD
Longitudinal Section
Elevation
Plan
End Elevation
Crown of Finished Road
Slope 1½:1
Bill of Material:-
Bars | No. | Size | Length
a | 260 | ½" sq | 5'-0"
b | 21 | " | 18'-0"
b1 | 9 | " | 18'-6"
h | 4 | " | 4'-0"
h1 | 5 | " | 8'-6"
h2 | 4 | " | 21'-0"
h3 | 34 | " | 22'-0"
V | 76 | ⅜" sq | 3'-0"
V1 | 6 | " | 7'-0"
V2 | 46 | ¾" sq | 9'-0"
V3 | 51 | ⅝" sq | 11'-0"
h4 | 3 | ⅜" sq | 3'-6"
m2 | 5 | ¾" sq | 6'-0"
t | 6 | ½" sq | 3'-0"
h1 | 46 | ¾" sq | 7'-6"
Z | 51 | ½" sq | 4'-0"
V4 | 10 | ⅜" sq | 6'-0"
V5 | 16 | " | 4'-0"
Steel - Lbs. 4960
Concrete Cu. Yds. 67.0
CEMENT WORLD

DESIGN AND CONSTRUCTI N OF SPECIAL HIGHWAY DRAINAGE STRUCTURES.

Reinforced Concrete Culvert to Bring Water Down to Lower Level. Conditions Requiring This Type of Culvert Are Common in McDonough County, Illinois, Where This Design Was Developed in State Aid Highway Drainage Work.



Storage Cellar with a Capacity of 800 Bushels. Greater or Less Capacity Can Be Secured by Adding to or Taking from the Length of the Plan, Each Additional Foot of Length Increasing the Storage Capacity 40 Bushels.



Construction Details of a Reinforced Concrete Tank Designed to Hold 6,000 Gallons of Oil.



Details of Concrete Swimming Pool.



Plans for a Concrete Dipping Vat for Cattle, as Recommended by the U. S. Department of Agriculture.



ARCHITECT'S OR BUILDER'S TABLE.

STOCK BILL FOR OFFICE TABLE

Top, 1 piece, 1⅛ by 38½ by 85 inches, S-2-S.
Top end rails, 2 pieces, 1½ by 3¼ by 38 inches, S-2-S.
Bottom end rails, 2 pieces, 1½ by 4¼ by 32½ inches, S-2-S.
Cleats, 2 pieces, 1½ by 2½ by 32 inches, S-2-S.
Stretcher, 1 piece, 1½ by 7¼ by 70 inches, S-2-S.
Slats, 2 pieces, ¾ by 9¼ by 26 inches, S-2-S.
Slats, 4 pieces, ¾ by 5¾ by 26 inches, S-2-S.



ARM CHAIR.

STOCK BILL FOR CHAIR

Front posts, 2 pieces, 1¾ by 1¾ by 26 inches, S-4-S.
Back posts, 1 piece, 1¾ by 5½ by 37 inches, S-2-S.
Seat rails, 2 pieces, ⅞ by 2½ by 18 inches, S-2-S.
Seat rail, 1 piece, ⅞ by 2½ by 21½ inches, S-2-S.
Seat rail, 1 piece, ⅞ by 3⅛ by 19½ inches, S-2-S.
Lower rails, 2 pieces, ⅝ by 1¾ by 18 inches, S-2-S.
Seat, 4 pieces, ⅝ by 4¾ by 24 inches, S-2-S.
Arms, 2 pieces, 1½ by 3 by 21 inches, S-2-S.
Back, 1 piece, 1 by 2¼ by 25½ inches, S-2-S.
Back slats, 2 pieces, ½ by 2¾ by 19 inches, S-2-S.
Back slats, 3 pieces, ½ by 1⅝ by 19 inches, S-2-S.

STOCK BILL FOR DRAFTING TABLE

Top, 1 piece, ⅞ by 24½ by 36½ inches, S-2-S.
Posts, 4 pieces, 1¾ by 1¾ by 40½ inches, S-4-S.
Side paneling—
Rails, 2 pieces, ¾ by 3¼ by 20 inches, S-2-S.
Rails, 2 piece, ¾ by 2¾ by 20 inches, S-2-S.
Munting, 2 pieces, ¾ by 3¾ by 26½ inches, S-2-S.
Panels, 4 pieces, 5/16 by 8½ by 25½ inches, S-2-S.
Back paneling—
Rail, 1 piece, ¾ by 3¼ by 32 inches, S-2-S.
Rail, 1 piece, ¾ by 2¾ by 32 inches, S-2-S.
Munting, 2 pieces, ¾ by 2¾ by 26½ inches, S-2-S.
Panels, 3 pieces, 5/16 by 9 by 25½ inches, S-2-S.
Facing, 1 piece, ¾ by 2⅜ by 32½ inches, S-2-S.
Slide, 2 pieces, ¾ by 1¾ by 22 inches, S-2-S.
Slide, 2 pieces, ¾ by 1¾ by 33 inches, S-2-S.
Slide, 1 piece, ½ by 16 by 28 inches, S-2-S.
Drawer supports, 14 pieces, ⅞ by 2½ by 20 inches, S-2-S.
Drawer supports, 14 pieces, ⅞ by 2½ by 32½ inches, S-2-S.
Drawer guides, 14 pieces, ¾ by ¾ by 20 inches, S-2-S.
Drawer fronts, 6 pieces, ¾ by 4¼ by 30½ inches, S-2-S.
Drawer ends, 12 pieces, ½ by 4¼ by 20 inches, S-2-S.
Drawer backs, 6 pieces, ⅜ by 4 by 30 inches, S-2-S.
Drawer bottoms, 6 pieces, ⅜ by 20 by 30 inches, S-2-S.



DRAFTING TABLE WITH DRAWERS



LIBRARY OR STUDY TABLE.

STOCK BILL FOR LIBRARY TABLE

Top, 1 piece, 1 by 30½ by 45½ inches, S-2-S.
Legs, 4 pieces 2½ by 2½ by 29½ inches, S-4-S.
Back rail, 1 piece, ¾ by 5¼ by 37 inches, S-2-S.
End rails, 2 pieces, ¾ by 5¼ by 26 inches, S-2-S.
Front rail, 1 piece, ¾ by 2 by 37 inches, S-2-S.
Shelf, 1 piece, ¾ by 11¼ by 40 inches, S-2-S.
Drawer facings, 2 pieces, ¾ by 3¼ by 16 inches, S-2-S.
Drawer sides, 4 pieces, ⅜ by 3¼ by 26 inches, S-2-S.
Drawer backs, 4 pieces, ⅜ by 3 by 16 inches, S-2-S.
Drawer bottoms, 2 pieces, ⅜ by 26 by 16 inches, S-2-S.
Drawer slides, 3 pieces, ¾ by 2¾ by 26 inches, S-2-S.
Drawer guides, 3 pieces, ¾ by 1½ by 26 inches, S-2-S.
Tie, over drawers, 1 piece, ½ by 2¾ by 36 inches, S-2-S.

The remaining pieces, keys, and short facings about the drawers may be got from scrap stock.



Construction Details of a Strong and Serviceable Piano Bench.

STOCK BILL FOR PIANO BENCH, GIVING FINISHED SIZES

Cover, 1 piece, ⅞ by 15½ by 40.
Posts, 4 pieces, 1¾ by 1¾ by 18¾ (one 1-inch tenon).
Frame, 2 pieces, ¾ by 4 by 37¾.
2 pieces, ¾ by 4 by 13½.
Lower rail, 2 pieces, 1¾ by 1¾ by 13½.
Stretcher, 1 piece, ¾ by 4 by 35⅛ (two ⅞-inch tenons).
Blocks, 4 pieces, ⅝ by 1½ by 1½.
Bottom, 1 piece, 5/16 by 12 by 36¼ (wallboard).
2 pieces, ⅜ by ⅜ by 33⅜.
2 pieces, ⅜ by ⅜ by 9⅛.
Hardware, 1 pair ¾ by 2½ nickel plated butts.
16 1½-inch No. 10 F. H. screws.



Working Details of a Cedar Chest of Unique and Attractive Design

INDEX TO ARCHITECTURAL DETAILS

For Every Type of Building

A Collection of Authoritative Plates for Contractors, Builders, Lumber Dealers, Millmen, Draftsmen, and Architects

Page

Accordian Doors, Design and Details 75
Adjustable Shelving for China Case 72
Alcove for Living Room, Design and Details 31
Anchoring Barn Superstructure to Concrete Foundations 126
Anchoring Roof Trusses to Side Walls in Plank Frame Barns 129
Anchoring to Concrete Foundations 74
Anchors, Wood Sills, to Concrete 65
Architect's Drafting Table and Filing Cabinet 154
Architectural Drafting Methods 3
Area Walls of Concrete 65
Arm Chair, Design and Construction of 154
Art Glass Windows 66
Asbestos Board for Fire Stopping 11
Asbestos Shingles, Use of 76
Ash Dump for Fireplaces 9
Ash Pit Under Fireplace 69
Attic Living Room, Design and Details of 32
Attic Remodelling 32
Balloon Framing, Shrinkage Settlement in 13
Balusters for Stucco Porch 42
Bank Building, Arrangement and Details of 116
Bank Front of Terra Cotta 117
Barn Construction, Fireproof 144
Barn Construction, Heavy Timber 139
Barn Construction, Monitor Roof Type 142
Barn Door Details 124
Barn Door, Sliding 124
Barn Roofs, Gothic Type 121
Basement Wall of 12-inch Tile, Details of 22
Basement Window Details 65
Basket Pattern for Brick Floors 25
Bay Window, Buffet 53
Bay Window, Octagon 36
Beaded Ceiling Plancier 63
Beams, Ceiling 71
Bed, Folding, or Disappearing 78
Bench for Piano, Hand-Made 155
Benches, Built-in, for Kitchen Nook 38
Bevel Wainscot 69
Blocking in Elevation 5
Blocking in Plans 4
Blocking in Rooms 3
Bonding Corners in Hollow Tile Walls 20
Book Case and Book Shelves 68
Book Case and Built-in Seat Combined 35
Book Case Built into Fireplace Alcove 35
Book Case Built Under Stairs 34
Book Case Colonial Built-in, Design and Details 48
Book Case Buffet Combination for Room Separation 37
Book Case with Open Shelves 53
Box Cornice 11
Box Cornice Construction 6, 42
Box Culvert to Drop Elevation of Water Without Scouring the Soil 148
Box Seat, Cedar Lined 32
Box Sill Construction 6
Braced Rafters 26
Bracing for High Corn Cribs 119
Bracing Latteral for Trusses 104
Brackets, Heavy Timber, Ornamental 41
Breakfast Nook, Design and Details of 38
Breakfast Nook Seat and Kitchen Cupboard, Back to Back 39
Brick and Stone Mantel 61
Brick and Tile in Combination 22
Brick Construction for Residences 19
Brick Corners for Hollow Tile Walls 20
Brick Fireplace Design and Details 47
Brick Fireplace with Book Shelves 47
Brick Fireplace with Built-in Book Cases 64
Brick Over Hollow Tile 17
Brick Paneled Mantel 77
Brick Pavement for House Entrance 41
Brick Pavement, Ornamental 41
Brick Porch with Wood Columns 47
Brick Veneer Construction 47

Page

Brick Veneer Construction, Over Sheathing 16
Brick Veneer Over Braced Wood Frame Without Sheathing 18
Brick Walls with Mineral Wool Filler at Eaves and Floors 11
Bronze Grill Work for Banks 116
Buffet and Book Case Combined Back to Back 37
Buffet on Either Side of French Doors 54
Buffet, Recessed in Small Bay 53
Buffet with Separate China Cabinet Above 36
Buffet with Windows 72
Builder's Hardware Details 82
Builder's Office Table, Design and Construction of 154
Building on a New Brick Porch 55
Built-in Cases for Attic Room 32
Built-in Furniture for the Home 68
Built-in Settle for Fireplace Alcove 31
Built-in Table and Seats for Kitchen 38
Bungalow Cornice, Open Rafter 67
Bungalow Stairway, Design and Details 45
Butler's Pantry, Design and Details of 40

Carrier Track Support in Barns 133
Cart for Cattle Feeding 143
Casement Details, Inward Opening 84
Casement Details, Outward Opening 85
Casement Windows, Divided Lights 38
Casement Windows, Outward Opening 65
Cashier's Cage, Details of 116
Cattle Dipping Vat of Concrete 153
Ceiling Beams 71
Ceiling Beams of Wall Board 29
Ceiling Construction, Fire-Resisting, for Basements 10
Ceiling Cove with Picture Mould, Two-Piece 64
Cement Floors for Cellars 65
Chimney Caps, Ornamental 70
Chimney Construction 9
China Cabinet Between Windows, Projecting 40
China Cases for Bulter's Pantry 40
China Closet Colonnade 54
Cinder Fill Under Porch 47
Coat Hanger Rod 69
Cold Storage Plant, Design and Details 112
Colonial Book Case, Projecting 48
Colonial Book Case, Recessed 48
Colonial Entrance 5, 70
Colonial Porch with Both Brick and Stave Columns 43
Colonnade Posts, Heavy, Eight Sided 35
Colonnade with Built-in China Closet 54
Columns of Wrought Iron in Barns 129
Columns, Stave for Colonial Porch 43
Combined Kitchen Cupboard, Cooler and Sink 78
Combined Kitchen Dresser and Library Book Case 68
Complete Working Plans for Eight-Room Dutch Colonial House 60
Complete Working Plans for Six Room Residence 56
Concrete Blocks, Standard Construction Details 25
Concrete Construction for Fireproof Barn 144
Concrete Floor for Hog House 137
Concrete Footings and Foundation for Brick Houses 19
Concrete Footings for Cottages 73
Concrete Footings for Hollow Tile Barn 143
Concrete Foundation Forms 74
Concrete Foundation Forms for Farm Buildings 142
Concrete Foundation Walls 80
Concrete Post Foundations 73
Concrete Swimming Pool, Construction of 155
Conservatory or Sun Parlor, Design and Details of 92
Continuous Trim in Living Room 51
Contour of Manger, Stall and Gutter for Concrete Stable Floors 121
Cork Brick for Stall Floors 124
Corn and Grain Elevator 145
Corn Crib and Hog House Combined 146
Corn Crib, Gambrel Roof, Construction of 118
Corn Crib, High Gable Roof, Construction of 118
Corn Crib, Small 144
Corn Crib, Two Stories 145

Page

Corn Feeder 137
Corner Construction for Hollow Tile Walls.... 20
Corner Porch of Brick.... 55
Corner Post Details 124
Corner Trellis 46
Cornice Mould, Five Member.... 71
Cornice Mould, Heavy 35
Cornice Mould of Six Members.... 66
Cornice Mould, Three Member.... 71
Cornice Mould, Two Piece.... 80
Cornice Mould with Ornamental Brackets.... 77
Crack-proof Wood Construction.... 14
Crib, High, Construction of....145
Cross Bonding, Face Brick Over Tile.... 22
Cross Section, Story and a Half House, Showing Standard Heights 56
Culvert, Box of Reinforced Concrete....149
Culvert, Double Box, for Long Span, Limited Clearance 150
Culvert of Reinforced Concrete....148
Curved Inglenook with Open Book Shelves.... 53
Curved Rafters, Built Up....121
Dairy Stable Floors of Concrete, Cows Facing In....125
Dairy Stable Floors of Concrete, Cows Facing Out...127
Daylight Factory, Design and Construction....105
Decorative Wood Inserts on Plaster.... 34
Design and Construction of Special Highway Drainage Structures....148, 149, 150, 151
Design Millwork to Fit Stock Hardware.... 82
Details of Bank Trim....116
Details of Floor Plans.... 4
Development of Details 6
Development of First Floor Plan.... 3
Development of Front Elevation.... 5
Development of Perspective 7
Diagonal Pattern for Floor of Square Tile.... 25
Diagonal Sheathing 15
Diagonal Sub-floors 15
Dining Room Buffet 68
Dining Room Buffet Connected with Kitchen Cabinet. 39
Dining Room Interior, Design and Details.... 36
Dipping Vat for Cattle, of Concrete....153
Display Cases for Stores.... 99
Display Windows for Stores.... 24
Doors, Five Cross Panel.... 69
Doors, Ice House....111
Doors, Two Panel.... 69
Doric Porch Columns.... 43
Dormer Construction 67
Double Box Culvert, Designed to Reduce the Cost of a Long Span Necessary Because of Limited Vertical Clearance 150
Double Fireplace Details.... 12
Double Hung Window Construction.... 6
Drafting Table with Drawers, Design and Construction of 154
Draftmen's Conventions 4
Drain Tile Outside of Footings.... 81
Drawer Case for Architect's Office....154
Drawer Construction for Buffet.... 36
Dresser, Kitchen, Details of.... 39
Drop-Front Compartments for Wardrobes.... 52
Drop Girt Framing, Shrinkage Settlement in.... 13
Drop Siding for Summer Cottages.... 73
Eaves Trough, Galvanized Iron.... 42
Electric Lighted Newel Posts.... 64
Elevation Details, Typical.... 5
Elevator for Corn Crib....145
Enclosed Porch, Design and Details of.... 93
End Bracing for Gothic Roof Barns....121
End Framing of Plank Frame Barn....127
Face Brick and Stucco Combination.... 47
Factory Building, Heavy Timber Construction, Design and Details 106
Factory Building, Reinforced Concrete, Design and Details 105
Farm Ice House, Construction of....110
Feed Troughs 137-142
Feed Truck for Dairy Barn, Details of....143
Feed Yard Equipment 137
Fence Details, Ornamental.... 90
Fire Guards Above Furnace.... 10
Fire Guards Around Heating Pipes.... 10
Fireplace Alcove, Design and Details of.... 35
Fireplace Construction 9
Fireplace Construction, Fire-Resisting and Smoke-Proof 96

Page

Fireplace Design in Tile and Bronze.... 31
Fireplace, Smokeless 75
Fireproofing Brick Houses, by Means of Metal Lumber 23
Fireproof Residence Details 76
Fire Protection Around Floor Registers.... 10
Fire-Retarding Details of Construction.... 8
Fire Stopping Around Chimneys.... 9
Fire Stopping Around Sliding Door Pockets.... 11
Fire Stopping in Brick Construction.... 12
Fire Stopping with Wood Blocks.... 8
Fire Stops at Roof Plate.... 8
Fire Stops at Floor Line.... 8
Fire Stops at Sill.... 8
Fire Stops in Frame Buildings.... 8
Flashing Around Chimneys.... 9
Floor Drains for Hog House....137
Floor Plan Elaboration 4
Floor Plan Suggestions for Display Windows.... 24
Floor Plans in Detail of Six-Room Residence.... 57
Floors of Reinforced Concrete and Tile.... 76
Floors, Rough and Finished.... 65
Floor Slabs, Combination Tile and Reinforced Concrete 104
Floor Slabs, Reinforced Concrete....104
Floors of Tile and Brick.... 25
Flour Bin, Details.... 39
Flower Box Details 70
Flower Box for Sun Porches.... 30
Flower Boxes, Tin or Copper Lined.... 76
Flue Lining Tile.... 9
Folding Bed, Built-in.... 78
Forms for Barn Foundations....142
Forms for Concrete Chimney Cap.... 74
Forms for Concrete Foundations.... 74
Forms, Temporary, for Building Tile Lintels.... 21
Foul Air Shaft in Hollow Tile Barns....138
Framing Around Doors and Windows, Brick Veneer Without Sheathing 18
Framing Around Doors and Windows in Brick Construction 19
Framing Around Windows and Doors in Brick Veneer 16
Fresh Air Duct in Hollow Tile Barns....138
Front Doors, Eight Light.... 54
Front Elevation of Modern Frame House.... 56

Gable or End Bracing for Plank Frame Barns....129
Gambrel Roof Barn Construction, Braced Rafter Type.123
Gambrel Roof House, Design and Details.... 60
Gambrel Roof, Self-Supporting 147
Gates, Ornamental 91
Girder and Post, Wood, for Basement.... 61
Girder with Wood Trusses.... 74
Girders, Wood, Steel, Concrete, Comparison of.... 14
Glass Setting for Store Fronts.... 97
Good and Bad Carpentry Contrasted.... 26
Gothic Roof Barn, Construction of....121
Grain Bin, Hen House....113
Grain Bins, Hopper Bottom....145
Grills and Screens of Ornamental Iron.... 95
Grill Work, Bronze, for Banks....116
Grounds for Wood Inserts, Plaster Walls.... 34
Group Windows 60
Gutter Concealed, for Box Cornice.... 11
Gutter Galvanized Iron Hanging.... 42
Hand Car to Run on Track in Dairy Barn....143
Hand Rail Details 72
Handy Cart for Feeding Silage....143
Hardware Details 82
Hardware Details, Accordian or Four-Fold Doors.... 87
Hardware Details, Doors to Fold into Flush Pockets. 86
Hardware Details, Double Door, Open In.... 82
Hardware Details, Double Door, Open Out.... 82
Hardware Details, Double Door, Open Out, Using Narrowest Cylinder Front Door Lock.... 82
Hardware Details, Double Door, Using Regular 3½-inch Inside Lock.... 83
Hardware Details, Double Doors to Open Out.... 88
Hardware Details, Double Doors to Open Out for Schools, Churches, etc.... 88
Hardware Details, Double French Window Having Rabbetted Lock, Bit Key or Thumb Bolt.... 83
Hardware Details, Double French Window, Opening In 83
Hardware Details, Double French Window, Opening Out 83
Hardware Details, Horizontal Pivoted Transom.... 89

Page

Hardware Details, Inward Opening Casement..... 84
Hardware Details, Open In, Using Narrowest Cylinder Front Door Lock..... 82
Hardware Details, Outside Blinds..... 89
Hardware Details, Outward Opening Casement Windows 84
Hardware Details, Parallel Sliding Doors..... 88
Hardware Details, Sideboard 85
Hardware Details, Single and Double Sliding Doors.. 86
Hardware Trimmers, Short Hand Form for Listing Hardware Items 85
Harness Cabinet, Design and Detail.....127
Hay Carrier Track Support.....123
Hay Chute and Manger for Stock Barns.....135
Hay Chute Detail, Automatic Closing.....124
Hay Rack for Horse Stalls.....124
Hay Track Arrangement in Round Barn.....120
Hay Track Support 147
Header Courses for Bonding..... 19
Headers and Trimmers Around Fireplace..... 9
Hearth Detail, Brick..... 9
Heavy Ceiling Beam Detail..... 35
Heavy Timber Entrance Details..... 41
Heavy Timber Framing for Barns.....139
Hen House, Open Front.....113
Herringbone Pattern for Brick Floors..... 25
Hinged Table 79
Hog House, Modified Saw Tooth, Construction of.....114
Hog House, Saw-Tooth Roof Type.....115, 137
Hog House, Saw-Tooth Roof, Construction of..... 137
Hog House with Concrete Yards, Design and Construction of 115
Hollow Tile Barn, Details of.....143
Hollow Tile Construction, Interlocking.....138
Hollow Tile Details 20
Horse Barn Details 124
Horse Stall Details 124
Horse Stall Partitions, Double Thickness.....126
Horse Stall Partitions, 2 by 6-inch Plank.....126
How to Build a Library Table.....155
How to Build a New Brick Porch..... 55
How to Make a Serviceable Piano Bench.....155

I-Beam Support for Porch Roof..... 43
Ice House and Cold Storage Plant.....112
Ice House of Wood, Design and Details.....110
Incubator Room, Arrangement of.....113
Ingle Nook in Living Room, Design and Details..... 50
Ingle Nook with Open Shelves, Design and Details... 53
Insulating for Ice Houses.....111
Interlocking Hollow Tile Construction.....138
Iron Doors, Ornamental..... 94

Jamb Details for Hollow Tile..... 20
Joist Hangers, Wrought Iron..... 21
Joist Headers, Doweled 26
Joist Supports for Hollow Tile Walls..... 21

Kitchen Cabinet and Dining Room Buffet, Back to Back 39
Kitchen Cabinet, Design and Details of..... 39
Kitchen Cooler 78
Kitchen Cupboard Lighted at Center by Casement Window 68
Kitchen Dresser on One Side of Partition, Library Book Case on Other..... 68

Ladders, Sliding for Stores..... 99
Large Kitchen Cupboard..... 58
Lattice Screen for Under Porch..... 42
Lattice Treatment for Sun Porch, Inside Trim..... 30
Lattice Truss, Wooden for Garage Roofs.....104
Lattice Work for Ornamental Fences..... 91
Laundry Layout 61
Laying Out a Wall Board Job..... 27
Lead Glass Windows for Built-in Cases..... 36
Light Construction for Summer Cottages..... 79
Linen Case, Design and Details.....101
Lintels of Hollow Tile Reinforced with Concrete and Steel 20
Lintels Over Doors and Windows of Tile Built with Reinforced Concrete 76
Living Room with Ingle Built-in Case and Semi-Open Stair 50
Lodge Hall, Design and Details.....109
Lumber Yard Shed.....113

Mantel Design in Quarry Tile..... 69
Mantel in Brick and Stucco..... 50
Manual Training Work.....155-156

Page

Medicine Case Details..... 64
Medicine Case with Drawers Below..... 66
Metal Batten Detail 138
Metal Lumber Details 23
Metal Lumber for Floors..... 23
Metal Shield for Smoke Pipe Passing Through Wood Partition 10
Mill Construction, Heavy Timber.....106
Mineral Wool Fire Stops..... 8
Mirror Doors for Wardrobes..... 52
Mirror for Buffet Back..... 37
Monitor Roof Barn, Construction of.....142
Monitor Shed for Lumber Yard.....113
Mullion Transom Front Entrance Frame..... 25
Mullion Windows, Designs for..... 60

Nests, Hen House.....113
New Brick Porch Remodels Old House..... 55
Newel Cap, Egyptian 44
Newel Cap, New Art..... 44
Newel Cap, Ornamental, Pressed..... 69

Openings in Hollow Tile Walls..... 20
Open Stairway, Design and Details of..... 33
Ornamental Gates and Fences..... 90
Ornamental Iron Porch Rail..... 43
Ornamental Rafter Ends 55
Orthographic Perspective Rendering, Pen and Ink.... 7

Paneled Back for Built-in Seats..... 38
Paneled Doors for Book Case..... 37
Pantry, Butler's or Serving..... 40
Pantry Case, Design and Details.....101
Parliament Butts, Use of..... 84
Partitions for Stock Pens.....136
Partitions of Wood Construction for Hog Houses....114
Party Wall, Separation of Wood Cornice..... 12
Pedestal Colonnade with China Closets Built In..... 54
Pergola Trellis 46
Perspective Drawing, Elements of..... 7
Piano Bench, Hand-Made, Design and Construction of.155
Picture Mould at Ceiling Line..... 35
Picture Theater, Design and Details.....107
Plancier Plaster for Box Cornice..... 42
Plank Floors, Removable, for Hog Houses.....114
Plaster Arch for Ingle Nook..... 53
Plaster Column for Stair Newel..... 34
Plaster, Plancier, for Box Cornice..... 42
Plate Rail, Four-Piece 64
Plate Rail with Ornamental Brackets..... 77
Plate Warmer, Steam Radiator..... 40
Platform Scale, Shed for.....144
Platform Stairway 72
Platform Stair, Design and Details..... 44
Pool, Swimming, of Concrete Construction.....153
Porch Columns, Square Box..... 67
Porch Construction with Colonial Columns..... 65
Porch Steps 65
Porch Steps, Wood..... 65
Porch with Both Brick and Stave Columns..... 43
Potato Cellar of Reinforced Concrete.....152
Poultry House, Design and Details of.....113
Purlin Plate Construction, Plank Frame Barns.....129
Purlin Posts, Heavy Timber.....139

Radiator Cover as Window Seat..... 30
Radiator Cover, Wood Seat..... 36
Rafters, Ornamental 55
Reinforced Concrete Box Culverts, of Span 12 Feet or Less, and Height 9 Feet or Less.....149
Reinforced Concrete Culvert to Bring Water Down to a Lower Level.....151
Reinforced Concrete Tank to Hold Oil.....152
Reinforcing for Columns and Girders.....105
Reinforcing for Hollow Tile Lintels..... 20
Remodeling an Old House by Building on a New Brick Porch 55
Remodeling the Old House..... 55
Remodeling the Old Porch..... 55
Road Culvert, Concrete 148
Road Culvert, Double Box.....150
Road Culvert of Reinforced Concrete.....149
Rod for Suit Hangers in Wardrobe..... 52
Roof Boards, Collar Beams..... 63
Roof Construction of Concrete and Tile..... 76
Roof Dormer Details 67
Roof Ends, Ornamental 67
Roof Plate of Wood for Brick Houses..... 19

Page

Roof Windows for Hog Houses....114
Round Barn, Construction of....120
Rustic Construction for Summer Cottages.... 79

Scale Drawings of Eight-Room House.... 60
Scale Drawings of Story and a Half Residence.... 56
Scale House, Construction of....144
Screens, Hinged 76
Seat Back Paneled.... 45
Seats Built into Octagon Bay.... 36
Section Through Colonial House, Showing Standard Construction 63
Self-Feeder for Steers....137
Self-Supporting Barn Roof....147
Self-Supporting Barn Roof Construction, Braced Rafter Type 123
Self-Supporting Gambrel Roof Construction, Heavy Truss Type 127
Self-Supporting Gothic Barn Roof....121
Semi-Concealed Stairs 45
Semi-Open Stair from Living Room.... 34
Serving Pantry, Design and Details of.... 40
Shed for Lumber Yard....113
Shelf Pins, Brass 51
Shelf Slotted for Serving Pantry.... 40
Shelf Supports for Built-in Cases.... 48
Shelter for Farm Scale....144
Shelving for Drug Stores.... 98
Shelving for Dry Goods Stores.... 99
Shelving for Hardware Stores.... 99
Shelving for Shoe Stores.... 98
Shingled Side Walls.... 60
Shiplap Sheathing 79
Show Window Construction.... 97
Shrinkage in Horizontal Timbers.... 14
Shrinkage of Wood Frame.... 14
Sideboard for Dining Room.... 36
Sideboard in Dining Room with Slide to Kitchen.... 39
Side Elevations of Frame House.... 56
Side Framing of Plank Frame Barn....130
Silo Construction for Inside of Barn....120
Silo Roof Detail....141
Simple Buffet 64
Simple Kitchen Cupboard Design.... 64
Single Corn Crib, Construction of....144
Sink for Serving Pantry.... 40
Sketch Perspectives 3
Sketch Plans 3
Slide or Dish Pass from Kitchen to Dining Room.... 39
Sliding Roors, Details of, Hardware.... 86
Sliding Doors for Pass Pantry.... 39
Sliding Door Pockets, Fire-Resisting.... 11
Socket, Porch, Built-up Timber.... 42
Sockets, Studding 145
Spiked Construction Contrasted with Gained or Notched 26
Spiked Joists Cause of Cracks.... 26
Splice Joints for Heavy Timber Trusses....107
Stable Construction, Low Gable Roof....140
Stable Floors of Concrete for Dairy Cows....121
Stair Balusters to Ceiling.... 45
Stair Balustrade, New Art.... 34
Stair Balustrade, Straight Line.... 34
Stair Construction Using Stair Wedges.... 80
Stair Newels Extending to Ceiling.... 33
Stair Newel Post, Straight Line.... 44
Stair Stringer Details 80
Stair Tread and Stringer Details.... 34
Stair Wedges 80
Stairs with Built-in Seat.... 45
Stairway in Living Room, Design and Details of.... 33
Stairways, Reinforced Concrete 105
Stairway with Book Case, Design and Details.... 34
Stall Guards, Metal....133
Standing Trim, Elaborate.... 66
Steel Beams for Supporting Tile Lintels.... 21
Steel Sash Details 105
Steps to Porch.... 65
Stock Barn, Design and Construction of....134
Stock Feeder of Large Capacity....137
Stock Pens, Construction of....136
Stock Trim for Residence Work.... 61
Storage Cellar of Reinforced Concrete....152
Store Building, Design and Details of.... 97
Store Fixtures and Shelving, Built-in.... 99
Store Front Construction 24, 97
Structural Tile Details....20, 76

Page

Stucco Porch Columns with Wood Ornaments.... 42
Stucco Porch, Design and Details of.... 42
Studding Socket Detail....124
Studding Sockets 145
Suggestive Patterns for Tile Floors.... 25
Summer Cottage Construction.... 79
Sun Parlor, Stucco Construction, Design and Details of 92
Sun Porch Design and Details.... 30
Swimming Pool of Reinforced Concrete....153

Table, Architects' or Builders', Design and Construction of 154
Table, Built-in for Breakfast Nook.... 38
Table for Drafting Room, Construction of....154
Table, Hand-Made, Design and Construction of....155
Table, Hinged, for Summer Cottage.... 79
Table, Library, Construction of....155
Table, Monastary Style, for Breakfast Nook.... 38
Tank for Oil, of Reinforced Concrete....152
Terra Cotta Details for Bank Exterior....117
Theater Construction 107
Tieing Self-Supporting Roof to Tile Walls....143
Tile Barn with Self-Supporting Roof....143
Tile Floor Designs and Patterns.... 25
Tile Floor in Ingle Nook.... 50
Tile Mantel Design 35
Tiled Floor for Serving Pantry.... 40
Timber Construction for Light Manufacturing....106
Timber Entrance for a Brick House.... 41
Timbers, Rough Hewn, Ornamental.... 41
Tin Flashing for Stucco Porch Posts.... 42
Tread and Riser Details.... 80
Trellis Arch Over Window.... 46
Trellis Arch with Benches for Entry Door.... 46
Trellis for Vine 46, 55
Trellis for Wall 46
Trellis for Side Wall, Ornamental.... 55
Trim, Continuous 51
Troughs, Hog House of Concrete....114
Truss Over Cased Opening Supporting Partition Walls 81
Trussed Rafters for Self-Supporting Gambrel Roofs..123
Trusses, Bow String Lattice....102
Trusses, Flat, Wood Lattice....102
Trusses, Light Steel or Curving Roof....104
Trusses, Wood, for Theater Roofs....107

Underground Storehouse for Vegetables....152
Unequal Shrinkage Setlement, Reasons for.... 14
Upholstered Built-in Seat.... 31

Vat, Dripping, for Cattle....153
Vegetable Cellar of Reinforced Concrete....152
Ventilating Flues for Tile Barns....138
Ventilation System for Concrete Barn....144
Ventilators, Galvanized Iron....140

Wainscote Tile for Kitchen.... 39
Wall Board Details 27
Wall Board Finish, Elaborate Treatment.... 29
Wall Board Finish, Simple Treatment.... 27
Wall Board Finish, with Ceiling Beams.... 28
Wall Construction of Hollow Tile.... 21
Wall Ties, Metal, for Brick Veneer.... 18
Warehouse for Lumber Yard....113
Wardrobe for Bedroom, Built-in.... 52
Weather Shield Over Windows.... 70
"Western" Framing 15
"Western" Framing Which Eliminates Unequal Shrinkage Settlement 14
Wind Plugging at Eaves.... 11
Wind Stops Around Openings in Hollow Tile Walls... 22
Window Details for Octagon Bay.... 36
Window Frames for Dairy Barns....124
Window Frames in Hollow Tile Wall.... 22
Window Seat and Radiator Cover for Sun Parlors... 30
Windows, Art Glass 66
Windows, Display for Stores.... 24
Windows Double Hung 67
Windows Hinged at Top to Swing In.... 67
Windows, Hog House, Roof....114
Wood Block Floors for Cow and Horse Stalls....128
Wood Cornice on a Brick Wall.... 12
Wood Frames for Openings in Hollow Tile Walls.... 22
Wood Girder with Flitch Rods.... 74
Wood Girder with Truss Rods.... 74
Wood Paneling for Living Room.... 50
Wrought Iron Doors for City Bank.... 94
Wrought Iron Porch Rail.... 43